

# Fluke RLD2 Leak Detector Flashlight

## Technical Data



RLD2 in leak detection mode

### Features

Compact UV flashlight uncovers refrigerant leaks instantly.\* The RLD2 combines leak detection ability with a bright flashlight to illuminate dark areas along with a laser pointer to pinpoint a leak.

- Instantly highlights leak detection dyes
- White LED light with 100,000 hour life
- Leak detection made easy
  - Vivid UV refrigerant leak detector finds the fault fast
  - Laser pointer pinpoints leak location
  - Bright flashlight with three LEDs penetrates dark areas
  - Key chain carabiner for convenience

\*For use with standard leak detection dyes available in the market.








RLD2 with standard carabiner

## Specifications

- Six UV/Blue LEDs highlight leak detection dyes
  - For use with standard leak detection dyes available in the market
- Laser pointer locates center of UV/Blue field
- Three white LED flashlight with 100,000 hour LED life
- Operating temperature: 0 °C to 50 °C (32 °F to 122 °F)
- Includes detachable key chain carabiner and AAA batteries
- One-year warranty

## Functions

<p><b>First Mode</b> <b>Flashlight</b></p> <p>First press activates unit and it is in the <b>LAST mode</b> selected</p> <p><b>TRIGGER</b> press turns <b>ON</b> flashlight*</p> 	<p><b>Second Mode</b> <b>UV light and Laser light</b></p> <p>Second press changes unit to the <b>COMBO mode</b></p> <p><b>TRIGGER</b> press turns <b>ON</b> UV light and laser light</p> 	 <p><b>1</b> Press indentation on top of battery door and slide downward</p> <p><b>2</b></p> <p><b>3</b></p> <p>Battery access.</p>
<p><b>Third Mode</b> <b>UV light</b></p> <p>Third press changes unit to the <b>NEXT mode</b></p> <p><b>TRIGGER</b> press turns <b>ON</b> UV light</p> 	<p><b>Fourth Mode</b> <b>Laser light</b></p> <p>Fourth press changes unit to the <b>NEXT mode</b></p> <p><b>TRIGGER</b> press turns <b>ON</b> laser light</p> <p><b>NEXT</b> Press changes unit <b>BACK</b> to original flashlight</p> 	

\*By holding in **TRIGGER** and then pressing **MODE** button the unit **LOCKS** into **FLASHLIGHT** mode- next **TRIGGER** press will release **LOCKED** state. This only occurs for the **FLASHLIGHT** mode.

## Ordering information

**RLD2** Leak Detector Flashlight

### Included accessories

Key chain carabiner and batteries.

Standard leak detection dyes are not sold by Fluke.

**Fluke.** Keeping your world up and running.®

		<p>205 Westwood Ave Long Branch, NJ 07740 1-877-742-TEST (8378) Fax: (732) 222-7088 salesteam@Tequipment.NET</p>
---	---	--