

## 4-in-1 Test Tools

### Features



- 200AAC current capability
- Non-contact voltage (40-600VAC)
- Capacitance
- Low battery indication
- Overload protection on all ranges
- Integral lead storage
- Audible dangerous voltage warning on all ranges
- Auto power off
- Ergonomic hourglass shape
- Compact clamp head
- 2-year warranty

700 Series



**61-704**  
True RMS, backlight, vibration mode to verify AC voltage, harmonics indicator, max hold, CAT III - 1000V



**200 Amp Clamp/Multimeter**  
Use it for testing a variety of electrical parameters on branch circuits or at receptacles.



**Non-Contact Voltage Tester**  
Use it for one-touch indication of power without test leads.



**61-701**  
Frequency, data hold, max hold, CAT III - 600V



**61-702**  
Vibration mode to verify AC voltage, harmonics indicator, max hold, CAT III - 1000V



**Voltage Tester with Shaker**  
Use it for tactile feel of AC voltage.

### Accessories

Includes	
Carrying Case	C-700
Silicone Test Leads	TL-102



**Harmonics Tester**  
Use it to ensure that a circuit contains clean power, free of harmonic distortion.

700 Series Specifications	61-701		61-702 & 61-704	
	RANGE & RESOLUTION	BASIC ACCURACY	RANGE & RESOLUTION	BASIC ACCURACY
AC VOLTAGE	200.0/600 V	1.2%	2000m/200.0/750 V	1.2%
DC VOLTAGE	20.00/200.0/600 V	0.5%	2000m/200.0/1000 V	0.5%
AC CURRENT	200.0 A	3.0%	200.0 A	3.0%
RESISTANCE	200.0/200.0k $\Omega$ Scale	1.0%	200.0/200.0k $\Omega$	1.0%
CAPACITANCE	200.0 $\mu$ F	3.0%	200.0 $\mu$ F	3.0%
FREQUENCY	2.000k/20.00k/40.00k Hz (Auto)	0.1%	—	—

Jaw opening is 1.3" (33mm).