mondopad





Bright Ideas Made Brilliant

Phone: 866-94 BOARDS (26273) / (732)-222-1511 Fax: (732)-222-7088 | E-mail: sales@touchboards.com

Giant Touch Tablet for Your Conference Room

Present, annotate and collaborate on a giant tablet with meeting participants in the room and around the world.

An InFocus® Mondopad™ puts everything you need to visually present, capture and share ideas at your fingertips – all integrated into a single device.

The Mondopad combines the power and flexibility of an all-in-one PC with a giant touch display in an elegant and cost effective package. Mondopad is built around industry standards and leading technologies.

- Multi-touch high definition display in 55" and 70" sizes
- Flexible and expandable with built-in Windows PC
- O Digital interactive whiteboard and document annotation
- Business-class video conferencing
- O Share, view and control from your tablet or smartphone
- Full copy of Microsoft® Office ensures file compatibility
- O 70" backlit LED panel is thin, energy-efficient, and ultra-reliable

Specifications*

Display	INF5520	INF7020
Size	55"	70"
Resolution	Full HD 1920 × 1080	
Technology	CCFL LCD	LED edge lit LCD
Inputs	HDMI 1.3 × 2, VGA (HD15 VESA), Component, S-Video, Composite, RS232, RCA stereo audio × 2, 3.5 mm stereo mini-jack, USB Type-B to touch screen controller board	HDMI 1.3, VGA, 3.5mm audio in, RS232 In
Outputs	RCA stereo audio (L/R) output for sound bar or other external A/V system	RCA stereo audio (L/R) output for sound bar or other external A/V system, RS232 Out
Touch Screen	Multi-Touch touch screen system with support for 2 touch and Windows 7 gesturing Glass protection overlay for display surface USB connection to PC from touch system panel board	

PC	INF5520	INF7020
Processor	Intel® Core i5-2520m, QM67 chipset with support for AMT 7.1	
Memory	4 GB of DDR3	4 GB of DDR3, 8GB max
Hard Drive	SATA 6Gb/s SSD Intel 520 series 120GB	
LAN (2×)	802.3 10/100/1000 Base-T with Wake on LAN	
Wi-Fi	Dual band 802.11 a/b/g/n MIMO PCIe half mini card, 2.4 GHz with Intel, AMT support	
Input Connections	USB Type-A × 6 (4 on side of display,	USB 3.0, USB 2.0 × 4, eSATA/USB, CF Slot,
	2 on PC (1 used by camera), Ethernet (RJ45 × 2)	3.5 mm audio input, 3.5 mm microphone
		input, Ethernet (RJ45 × 2)
Output Connections	Optional USB 2.0 to HDMI adapter	DVI-I, DisplayPort S/P DIF, 3.5mm stereo
	(for display out)	audio out
Operating System	Windows 7 Pro 64bit	
Included Software	Microsoft Office Home & Business 32bit, Mondopad interface software	



^{**} Keyboard and/or mouse may not be shipped to all countries.



Resolution: 1280 × 720

Frame rate: 22 fps at HD with H.264+YUV (2-way)

Lens and Field of View: F/2.0, 3P Lens; FOV(D) 56.8° in HD mode, FOV(D) 50° in VGA mode 1.0× zoom, FOV(D) 30° in VGA mode 1.6× zoom

Audio support: 4 built-in Unidirectional microphones

Interface: USB 2.0 High Speed

Focus: Auto focus

Tilt: Manual up/down and left/right ±40°

Power via USB

Soundbar

Power: 60 Hz AC

Speaker Drivers (L&R): Two 3" and one 3/4" Aluminum Neodymium Tweeter (per side)

Power Output (RMS): 20 watts/channel @ 1% THD, 1KHz, 2-channels drive, 70 watts total system PEAK

Frequency Response: 90 Hz to 20 KHz

Accessories Included: Wireless keyboard (where allowed), wireless mouse (where allowed), cleaning cloth, VGA cable, USB cable, security screws, security screw removal tool, power cord, remote, quick setup guide, sound bar assembly, camera assembly, foot assembly Warranty: 1 year limited

Shipping Weight (INF5520):

Monitor, PC and camera: 136 lbs / 61.7 kg,

Sound Bar: 14.33 lbs / 6.5kg, Stand: 9.26 lbs / 4.2 kg

Shipping Dimensions (INF5520):

Monitor, PC and camera:

58.66 × 13.86 × 38.39 in / 1490 × 352 x 975 mm,

Sound Bar: $57.48 \times 7.08 \times 5.7$ in $/ 1430 \times 180 \times 145$ mm, Stand: 22.05 × 5.31 × 15.94 in / 560 × 135 × 405 mm

Shipping Weight (INF7020):

Monitor: 181 lbs / 82 kg, Sound Bar: 14.4 lbs / 7.7 Kg,

PC: 5.3 lbs / 2.4 kg, Feet: 9.26lbs/4.2 kg

Shipping Dimensions (INF7020):

Monitor: 71 × 11 × 44 in / 1803 × 279 × 1118 mm,

Sound Bar: $43 \times 7.25 \times 7.5$ in $/ 1092 \times 184 \times 191$ mm,

PC: $12 \times 6.5 \times 12$ in $/305 \times 165 \times 305$ mm, Feet: 22.05 × 5.31 × 15.94 in / 560 × 135 × 405 mm

Energy Star: 5.1 for display and PC

Operating Temperature: 5° to 35°C at 0 to 10K ft

Noise: < 40dBA @ 25℃

Approvals for INF5520:

UL and c-UL (US/Canada), FCC (US/Canada), CE (Europe), C-tick (Australia), CCC (China), KC (Korea), NOM (Mexico), BSMI (Taiwan)

Approvals for INF7020: UL and FCC (US)