

D.C. MILLI-OHM METER



GOM-801H



The GOM-801H milliohm meter is the ideal device for quick and precise component and material resistance measurements. The main display is equipped with a 3 1/2 digit 0.5" red LED with comparator indicators. Measurable objects can cover cable joints, earth bonds, switches, motors, transformers and generators. The front panel features seven selectable test ranges, 20m Ω to 20k Ω . The internal comparator is fully adjustable for the user settable Hi/Lo comparison indicator. The GOM-801H is the best choice for an inexpensive, easy to use, yet reliable milliohm meter.




205 Westwood Ave
Long Branch, NJ 07740
1-877-742-TEST (8378)
Fax: (732) 222-7088
salesteam@Tequipment.NET

FEATURES

- * Measures from 20m Ω ~ 20k Ω in 7 Ranges
- * 1A High Test Current
- * High Resolution 10 $\mu\Omega$
- * Hi/Lo Comparator Indicator and Buzz Alarm
- * 3 1/2 Digits 0.5" LED Display

GTL-108A Test Lead

For: GOM-801H/802 , GDM-8255A/8251A



SPECIFICATIONS

TEST RANGE	
	20, 200m Ω , 2, 20, 200 Ω , 2k, 20k Ω , 7 Ranges
TEST CURRENT (Test Voltage 0.2V)	
	20m Ω /200m Ω : 1A 2 Ω : 0.1A 20 Ω : 10mA 200 Ω : 1mA 2k Ω : 100 μ A 20k Ω : 10 μ A
ACCURACY	
Measuring	20m Ω \pm (0.2% rdg + 6 digits) 200m Ω ~ 20k Ω \pm (0.2% rdg + 4 digits)
Setting	\pm (0.2% + 6 digits)
RESOLUTION	
	0.01 , 0.1 , 1 , 10 , (\geq symbol) 100m Ω , 1 , 10
COMPARATOR	
	HI, LO settable
DISPLAY	
	3 1/2 digits 0.5" LED display HI, GO, LO indicator
POWER SOURCE	
	AC 100V/120V/220V/230V \pm 10% , 50/60Hz
DIMENSIONS & WEIGHT	
	230(W) x 95(H)x280(D)mm, Approx. 2 kg

ORDERING INFORMATION

GOM-801H High Precision Programmable DC Milli-Ohm Meter

ACCESSORIES :

User manual x 1 , Power cord x 1

Test Lead GTL-108A x 1



205 Westwood Ave
Long Branch, NJ 07740
1-877-742-TEST (8378)
Fax: (732) 222-7088
salesteam@Tequipment.NET