

# Fiber OWL / Dual OWL / BOLT Test Kit

Multi-mode Fiber Certification Test Kit  
with Optical Length Testing

## Overview

Many fiber optic network bids and Requests For Quote (RFQ) are citing cabling standards to specify the set of guidelines (such as fiber length) that the network installer must follow during the network installation. Adherence to such standards is meant to ensure the quality of the installation and guarantee that the network will perform as it was designed.

The process of testing a network installation to ensure its adherence to specified standards is called certification, and often requires hard-copy documentation as proof of adherence to standards.

The **Fiber OWL / Dual OWL / BOLT Test Kit** contains the tools necessary for certifying fiber optic links against a myriad of popular cabling standards in multi-mode networks.

The **Fiber OWL optical power meter** is multi-mode and single mode ready, and contains a user-friendly Fiber Link Wizard that performs link budget calculation, and sets a reference value using the characteristics of the link. This reference is the PASS/FAIL threshold and is calculated against the chosen standard. Up to 900 fiber runs may be stored, and serially downloaded to a PC for report generation using our OWL Reporter software.

The Fiber OWL is available in two configurations. The Fiber OWL 2+ has a measurement range of +5 to -70 dBm, and the Fiber OWL 2C+ has a measurement range of +25 to -50 dBm.

The **Dual OWL** is our NIST traceable multi-mode light source. Its dual wavelength outputs (850nm / 1300nm) are temperature-stabilized for accurate measurements. Two connector options are available (ST and SC).

The **BOLT** has multiple functions. It is a 1310nm laser light source designed to couple -10 dBm into single mode fiber. It also functions as a fiber link length tester. Optical measurement of a fiber link is very accurate, and ensures that fiber attenuation calculations are using the correct length. It also produces a 2-kilohertz modulated signal for use with fiber identifiers.



## Kit Contents

<b>Power Meter:</b>	Fiber OWL
<b>Light Source:</b>	Dual OWL
<b>Length Tester:</b>	BOLT
<b>Accessories:</b>	OWL Reporter software Product manuals Download cable 9-volt batteries NIST certificate Carrying case

Protective rubber boots for the Fiber OWL are not yet available.

## Features

- Certification of multi-mode fiber links at 850nm and 1300nm
- Data storage for up to 900 data points including run labels, fiber type, and link information including link name, date, reference power values, fiber length, and number of splices and interconnects
- Built-in loss wizard for calculation of maximum allowable loss values (link budget)
- RS-232 interface for continuous data logging, report printing, or data downloading
- OWL Reporter software for printing formatted fiber certification reports
- Absolute or relative mode for giving you instant pass/fail results
- Selectively view, delete or resample data points
- Optical measurement of fiber links up to 25 kilometers

### Supported Cabling Standards:

EIA/TIA 568-B	ISO/IEC 11801
1000Base-SX	1000Base-LX
100Base-FX	10Base-FB
10Base-FL	FDDI
ATM-155	ATM-622
Fibre Channel	Token Ring

Also supports 2 user-definable standards


### Additional Measurement Wavelengths:

980nm	1310nm	1480nm	1550nm
-------	--------	--------	--------

Product manuals come in PDF format on CD. Adobe Acrobat Reader™ is required to view these documents.



Patch cables are available for an additional charge. Call 262-473-0643 for more information.



# Fiber OWL / Dual OWL / BOLT Test Kit

Multi-mode Fiber Certification Test Kit

## Specifications

### Fiber OWL Optical Power Meter

<b>Detector Type</b>	Ge (2mm)
<b>Supported Fiber Types</b>	62.5/125 $\mu$ m multi-mode 50/125 $\mu$ m multi-mode 100/140 $\mu$ m multi-mode 7-9/125 $\mu$ m single mode
<b>Calibrated Wavelengths</b>	850nm, 980nm, 1300nm / 1310nm, 1550nm
<b>Additional Wavelengths</b>	1480nm
<b>Measurement Range</b>	+5 to -70 dBm (FO2+) +25 to -50 dBm (FO-2C+)
<b>Accuracy</b>	$\pm 0.15$ dB
<b>Resolution</b>	0.01 dB
<b>Battery Life</b>	up to 200 hours (9V)
<b>Connector Type</b>	2.5mm Universal
<b>Data Storage Points</b>	up to 900
<b>Download Data Points</b>	OWL Reporter Software
<b>Power Units Displayed</b>	dBm, dB, $\mu$ W
<b>Modes of Operation</b>	Simple / Certification
<b>Battery Capacity Display</b>	Yes
<b>Backlight</b>	Yes
<b>NIST Traceable</b>	Yes
<b>Auto-shutdown</b>	Yes
<b>Serial Port Diagnostic</b>	Yes
<b>Operating Temperature</b>	-10 to 55 C
<b>Storage Temperature</b>	-30 to 70 C
<b>Width</b>	3.48"
<b>Height</b>	6.48"
<b>Depth</b>	1.1"
<b>Weight</b>	373g (12 oz.)

### Dual OWL Multi-mode Light Source

<b>Launch Method</b>	LED
<b>Connector</b>	ST or SC
<b>Center Wavelength (850nm)</b>	850 $\pm 20$ nm
<b>Center Wavelength (1300nm)</b>	1290nm min 1350nm max
<b>Spectral Width (FWHM; 850 nm)</b>	35 nm
<b>Spectral Width(FWHM; 1300nm)</b>	170nm
<b>Output Power (62.5<math>\mu</math>m core)</b>	-20.0 dBm
<b>Initial Accuracy</b>	0.1 dB
<b>Fiber Type</b>	Multi-mode
<b>Battery Life</b>	40 hrs.
<b>Battery Capacity Display</b>	Yes
<b>Operating Temperature</b>	0 to 55° C
<b>Storage Temperature</b>	0 to 75° C
<b>Width</b>	2.75"
<b>Height</b>	4.94"
<b>Depth</b>	1.28"
<b>Weight</b>	154g

### BOLT Optical Length Tester

<b>Launch Method</b>	FP Laser
<b>Connector</b>	ST
<b>Center Wavelength</b>	1310 $\pm 30$ nm
<b>Spectral Width (FWHM)</b>	2nm
<b>Output Power (9 <math>\mu</math>m core)</b>	-10.0 dBm
<b>Initial Accuracy</b>	0.1 dB
<b>Fiber Type</b>	Single Mode
<b>Laser Drift</b>	0.05 dB (12 hours)
<b>Measurement Resolution</b>	up to 1 meter
<b>Measurement Accuracy</b>	$\pm 2.5$ meters
<b>Measurement Range</b>	25 kilometers
<b>Battery Life</b>	15 hours
<b>Battery Capacity Display</b>	Yes
<b>Operating Temperature</b>	0 to 55° C
<b>Storage Temperature</b>	0 to 75° C
<b>Low Battery Indicator</b>	Yes
<b>Modes of Operation</b>	Continuous Wave / 2kHz pulsed
<b>Width</b>	2.75"
<b>Height</b>	4.94"
<b>Depth</b>	1.28"
<b>Weight</b>	154g