SKU: KIT-MO-D285st SKU: KIT-MO-D285sc

Overview

Many fiber optic network bids and Requests For Quote (RFQ) are citing cabling standards to specify the set of guidelines (such as fiber length) that the network installer must follow during the network installation. Adherence to such standards is meant to ensure the quality of the installation and guarantee that the network will perform as it was designed.

The process of testing a network installation to ensure its adherence to specified standards is called certification, and often requires hard-copy documentation as proof of adherence to standards.

The *Micro OWL / Dual OWL 850 Test Kit* contains the tools necessary for certifying fiber optic links against the TIA-568-B.3 cabling standard in multimode networks.

The *Micro OWL optical power meter* is multimode and singlemode ready, and contains a user-friendly Fiber Link Wizard that performs link budget calculation, and sets a reference value using the characteristics of the link. This reference is the PASS/FAIL threshold and is calculated against the chosen standard. Up to 1000 fiber runs may be stored, and serially downloaded to a PC for report generation using our OWL Reporter software. Its universal port allows connections to ST, SC, and FC, and also includes a 1.25mm universal port for connection to LC, MU, and other SFF connectors.

The *Dual OWL 850* is our NIST traceable multimode light source. Its 850nm output is temperature-stabilized for accurate measurements. Two connector options are available (ST and SC).



Features

TIA-568-B.3 certification of multimode fiber links at 850nm

Data storage for up to 1000 data points including run labels, fiber type, and link information including link name, date, reference power values, fiber length, and number of splices and interconnects

Built-in loss wizard for calculation of maximum allowable loss values (link budget)

RS-232 interface for continuous data logging, report printing, or data downloading

OWL Reporter software for printing formatted fiber certification reports

Absolute or relative mode for giving you instant pass/fail results Selectively view, delete or resample data points

Kit Contents

Power Meter: Micro OWL
Light Source: Dual OWL 850

Accessories: OWL Reporter software

Product manuals Download cable 9-volt batteries NIST certificate Carrying case

Protective rubber boots



Product manuals come in PDF format on CD. Adobe Acrobat Reader $^{\rm IM}$ is required to view these documents.

Patch cables are available for an additional charge. Contact OWL for more information.



O. W. L. MANUFACTURER OF QUALITY OPTICAL FIBER TEST EQUIPMENT



Micro OWL/Dual OWL 850 Test Kit

SKU: KIT-MO-D285st SKU: KIT-MO-D285sc

Depth Weight

Specifications

opecinications		
Micro OWL Optical Power Meter		
Detector Type	Ge	
Calibrated Wavelengths	850nm, 1300nm, 1310nm, 1550nm	
Measurement Range	+5 to -70 dBm	
Accuracy	±0.15 dB	
Resolution	0.01 dB	
Battery Life	up to 100 hours (9V)	
Connector Type	2.5mm Universal	
Data Storage Points	up to 1000	
Download Data Points	OWL Reporter Software	
Power Units Displayed	dBm, dB, μW	
Battery Capacity Display	Yes	
Backlight	Yes	
NIST Traceable	Yes	
Auto-shutdown	Yes	
Operating Temperature	-10 to 55 C	
Storage Temperature	-30 to 70 C	
Width	3.48"	
Height	6.48"	

Dual OWL 850 Multimode Light Source		
Launch Method	LED	
Connector	ST or SC	
Center Wavelength	850 ±20nm	
Spectral Width (FWHM)	35 nm	
Output Power (62.5µm core)	-20.0 dBm	
Initial Accuracy	0.1 dB	
Fiber Type	multimode	
Battery Life	40 hrs.	
Battery Capacity Display	Yes	
Operating Temperature	0 to 55° C	
Storage Temperature	0 to 75° C	
Width	2.75"	
Height	4.94"	
Depth	1.28"	
Weight	154g	
Conforms to the Harmonized European Standards EN 61326-1 and EN 61010-1.		

Conforms to the Harmonized European Standards EN 61326-1 and EN 61010-1.

1.1"

373g (12 oz.)