

EX330 – Multimedia Projector

Bold, Bright and Brilliant

The EX330 is an ultra-portable, XGA digital projector for the road warrior from Optoma. Ideal for “grab and go” presentations, the Optoma EX330 is unparalleled in size, weight and connections. It also features BrilliantColor™ technology and a DLP® chipset from Texas Instruments for crisp and amazing picture quality.



Features

- Ultra portable 2.4lb DLP projector
- Native XGA resolution and HD compatible
- 2200 lumens and 2000:1 contrast ratio
- Connections include HDMI, VGA, s-video, composite video and USB
- Ideal presentation remote with laser pointer and page advance features
- Up to 5000 hours lamp life



Specifications

Display Technology
 Single 0.55" DMD DLP
 Technology by Texas
 Instruments

Resolution
 Native XGA (1024 x 768)

Maximum Resolution
 SXGA+ (1400 x 1050)

Brightness (Typical)
 2200 ANSI Lumens

Contrast Ratio
 2000:1 (Full On/Full Off)

Lamp Life and Type
 3000/5000 Hours (STD/ECO)
 165W UHP

Throw Ratio
 1.95-2.15:1 (Distance/Width)

Image Size (Diagonal)
 22.9" to 302" (0.58 to 7.67m)

Projection Distance
 3.3' to 39.37' (1.0 to 12m)

Remote Control
 Fully Featured Remote Control
 w/Mouse and Laser Pointer

Displayable Colors
 16.7 Million

Aspect Ratio
 4:3 Native, 16:9 Compatible

User Controls
 Complete On Screen Menu
 Adjustments in 22 Languages

Computer Compatibility
 VGA, SVGA, XGA, SXGA,
 SXGA+, WXGA Resized, VESA,
 PC and Macintosh Compatible

Video Compatibility
 NTSC, PAL, SECAM, SDTV
 (480i), EDTV (480p), HDTV
 (576i/p, 720p, 1080i/p)

Uniformity
 85%

Keystone Correction
 ± 18° Vertical

Horizontal Scan Rate
 15 to 100 kHz

Vertical Refresh Rate
 43 to 85 Hz

Projection Lens
 F=2.41-2.55, f=21.79~23.99mm,
 1.10X Manual Zoom and Focus

I/O Connectors
 HDMI, VGA-In, Composite
 Video, S-Video, USB

Security
 Kensington® Lock Port

Projection Method
 Front, Rear, Ceiling Mount,
 Table Top

Weight
 2.4 lbs (1 kg)

Dimensions (W x H x D)
 8" x 2.5" x 6.1"
 (205.5 x 64 x 156 mm)

Noise Level (STD/ECO)
 33dB/31dB

Power Supply
 AC Input 100-240V,
 Auto-Switching

Power Consumption
 225 Watts (Maximum),
 <10 Watts (Standby)

Operating Temperature
 41-95° F (5-35° C) (80%
 Humidity), Adjustable Fan Speed
 for High Altitude Application

Standard Accessories
 AC Power Cord, VGA to VGA
 Cable, Carrying Case, Remote
 Control, Batteries for Remote,
 Quick Start Guide, Warranty
 Card and User's Manual

Optional Accessories
 Ceiling Mount, S-Video Cable,
 VGA to Component Cable,
 Composite Video Cable, DVI to
 HDMI Adapter, HDMI Cable,
 Gold Service Warranty and
 Panoview™ Series Screens

Warranty
 1 Year Limited Parts and Labor,
 90 Days on Lamp

UPC
 796435 11 689 7

Accessory Part Numbers
 Lamp: BL-FP165A
 Remote: BR-5021L
 Case: BK-4022