



Phone: 866-94 BOARDS (26273) / (732)-222-1511 Fax: (732)-222-7088 | E-mail: sales@touchboards.com

Datasheet - TS400

TS400 - Multimedia Projector

Versatile & Designed to last

Optoma's TS400 digital projector combines performance and functionality to create the optimal blend of price and performance. Weighing in at 4.4 pounds, the robust and fully featured TS400 is a complete solution for a wide range of applications. From the boardroom to classroom, the TS400 excels!



- Native SVGA (800 x 600) resolution for sharp display
- Bright 2200 lumens for great image quality for a wide range of applications
- Superior 2000:1 contrast ratio for cinema quality images and crisp graphics
- SXGA+ (1400 x 1050) capability with high-end laptops
- Fully HDTV compatible (720p, 1080i)
- Convenient dual VGA-in, component, composite video, VGA-out and s-video inputs
- Weighs just 4.4 pounds
- User password security locking system
- Adjustable cooling fan speed for high altitude usage













Specifications

Briahtness 2200 ANSI Lumens

Resolution Native SVGA (800 x 600) SXGA+ (1400 x 1050) Max.

Contrast Ratio 2000:1 (Full On/Full Off)

Lamp Life and Type 2000/3000 Hours (STD/ECO) 200W UHP

Display Type 0.55" DDR DLP® Technology by Texas Instruments

Weight 4.4 pounds (1.9 kg)

Throw Ratio 1.93 - 2.13:1

Image Size (Diagonal) 24.6" to 306" (0.6 to 7.77 m)

Projection Distance 3.9' to 39.3' (1.2 to 12)

Audio One 2-Watt Speaker

Computer Compatibility XGA, SVGA, VGA, SXGA+, VESA, PC and Macintosh Compatible

Video Compatibility NTSC, PAL, SECAM, SDTV (480i), EDTV (480p), HDTV (720p, 1080i)

Horizontal Scan Rate 15 to 100 kHz

Vertical Refresh Rate 56 to 85 Hz

User Controls Complete Onscreen Menu Adjustments in 11 Languages

I/O Connectors Dual VGA-In, VGA-Out, S-Video, Composite Video, Audio-In, RS-232

Projection Lens F= 2.7~3.0, f=21.83~23.81mm, 1.2:1 Manual Zoom and Focus

Noise Level 28dB

Dimensions (W x H x D) 9" x 3.7" x 8.26" (230x 95 x 210mm)

Power Consumption 265 Watts (Maximum) <15 Watts (Standby Mode)

Power Supply AC Input 100 ~ 240V, **Auto-Switching Power Supply**

Standard Accessories AC Power Cord, VGA to VGA Cable, Composite Video Cable, Remote Control, Batteries for Remote, Lens Cap, Quick Start Guide, Warranty Card and User's Manual

Optional Accessories Ceiling Mount, S-Video Cable, 15-pin to 3 RCA Component/HDTV Adapter, Audio-Out Adapter and GrayWolfII™ Series Screen

Warranty 3 Years Optoma Express Replacement Service, 1 Year on Lamp

UPC 796435 11 122 9