



Key Features

- Easy-to-read text – Bright at 3500 ANSI lumens and high 3000:1 contrast ratio
- VGA and audio pass-thru operational on standby mode
- Auto keystone supports installation
- Remote management via RS-232 and Crestron management software
- Broad range of audio and video connectivity
- Wireless connectivity with optional dongle



The Optoma TX615-3D delivers exceptional brightness to overcome ambient light, making it the ideal choice for nearly any installation. Featuring a built-in 10-Watt speaker system and wired network management, the TX615-3D is equipped with the latest color and image processing technologies from Texas Instruments.

The 3D effect is generated by splitting this signal into two standard video streams, one for each eye. Using DLP Link™ technology, the 3D glasses synchronize with the image on screen to filter each stream to the correct eye. Your brain then combines the two streams to make them jump to life.

Detail Specifications

<p>Display Technology Single 0.55" DMD DLP Technology by Texas Instruments</p>	<p>Image Size (Diagonal) 27.5" to 303" (0.7 to 7.69m)</p>	<p>Video File Compatibility NTSC, PAL, SECAM, SDTV (480i), EDTV (480p), HDTV (720p, 1080i/p)</p>
<p>Resolution Native XGA (1024x768)</p>	<p>Aspect Ratio 4:3 Native, 16:9 and 16:10 Compatible</p>	<p>Uniformity 85%</p>
<p>Maximum Resolution UXGA (1600x1200)</p>	<p>Remote Control Full-Featured IR Remote with Laser Pointer and Mouse Functions</p>	<p>Projection Lens F= 2.4-2.55, f= 21.8-24mm, 1.1x Manual Zoom and Focus</p>
<p>Brightness 3500 ANSI Lumens</p>	<p>Keystone Correction ±40° Vertical</p>	<p>Loop Through Monitor: D-Sub 15-Pin VGA Output Audio: Stereo Mini-Jack Output (Functional in Both Normal and Standby Modes)</p>
<p>Contrast Ratio 3000:1 (Full On/Full Off)</p>	<p>Displayable Colors 1.07 Billion</p>	<p>User Controls Complete On-Screen Menu Adjustments in 23 Languages</p>
<p>Lamp Life and Type 4000/3000 Hours (STD/Bright) 230W P-VIP</p>	<p>Offset 115%</p>	<p>I/O Connectors HDMI, Two VGA-In, VGA-Out, S-Video, Composite Video, Three Stereo Audio-In, Stereo Audio-Out, 12v trigger, RJ45, RS-232 and USB</p>
<p>Throw Ratio 1.95 to 2.15:1 (Distance/Width)</p>	<p>Computer Compatibility UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized, VESA, PC and Macintosh Compatible</p>	
<p>Projection Distance 3.93' to 39.3' (1.2 to 12m)</p>		

Security

Keypad Lock, Kensington® Lock and Security Bar

Projection Method

Front, Rear, Ceiling Mount, Table Top

Weight

6.4 lbs (2.9kg)

Dimensions (W x H x D)

12.76" x 3.82" x 9.21" (324 x 97 x 234 mm)

Audio

10W Stereo Speakers

Noise Level

29dB/31dB

Horizontal Scan Rate

15.3 to 91.1 KHz

Operating Temperature

41 to 104°F (5 to 40°C), 80% Max Humidity

Power Supply

AC Input 100-240V, 50-60Hz, Auto-Switching

Power Consumption

328 Watts (Bright), 272 Watts (STD) <1 Watt (Standby)

Standard Accessories

AC Power Cord, VGA to VGA Cable, USB Cable, Remote Control, Batteries for Remote, Carrying Case, Lens Cap, CD-ROM User's Manual, Quick Start Card and Warranty Card

Optional Accessories

Ceiling Mount, Wireless Dongle, HDMI Cable, VGA to Component Cable, S-Video Cable, Composite Video Cable, RS-232 Cable and Panoview™ Series Screens, DLP 3D Glasses

Warranty

3 Year Optoma Express Replacement Service, 1 Year Lamp

UPC

796435 41 727 7

Vertical Refresh Rate

24 to 85 Hz, 120 Hz