



## Dazzle & Captivate Your Audience



The Optoma TX615 delivers exceptional brightness to overcome ambient light, making it the ideal choice for nearly any installation. Featuring a built-in 10-watt speaker system and wired network management, the TX615 is equipped with the latest color and image processing technologies from Texas Instruments.

### TX615 FEATURES


- ❑ Easy-to-read text – bright at 3500 ANSI lumens and high 3000:1 contrast ratio
- ❑ VGA and audio pass-thru operational on standby mode
- ❑ Filter-free design means lower cost of ownership
- ❑ Remote management via RS-232 or RJ45 connectivity
- ❑ Broad range of audio and video connectivity
- ❑ Wireless connectivity with optional dongle

# TX615 | Multimedia Projector

## Projection Distance/Image Size

Projection Distance (Feet)	Maximum Diagonal (Inches)	Minimum Diagonal (Inches)
6	46	42
8	62	56
10	77	70
12	92	84
14	108	98
16	123	112
18	138	126

## Control Panel



## Optional Accessories

Lamp:	BL-FP230D
Wireless Dongle:	BI-EXTGB
Remote:	BR-5030L
Power Cord (1m):	BC-PUPIXY01
Power Cord (11m):	BC-PUPIXY11
S-Video Cable (1.8m):	BC-SVSVXX02
Composite Cable (1.8m):	BC-COCOXX02
VGA Cable (5m):	BC-VGVGXX05
VGA to Component Cable (5m):	BC-VGCRXX05
VGA to Component Adapter:	BC-VGCRXY00
Ceiling Mount:	BM-5001U
Carrying Case:	BK-4028
100" Manual Pull-Down Screen:	DS-3100PMG+

## Specifications

Display Technology:	Single 0.55" DMD DLP® Technology by Texas Instruments
Resolution:	Native XGA (1024 x 768)
Maximum Resolution:	UXGA (1600 x 1200)
Brightness (Typical):	3500 ANSI Lumens
Contrast Ratio:	3000:1 (Full On/Full Off)
Lamp Type:	230W P-VIP
Lamp Life (STD/Bright):	Estimated at 4000/3000 Hours
Throw Ratio:	1.95 to 2.15:1 (Distance/Width)
Image Size (Diagonal):	27.5" to 303" (0.7 to 7.69 m)
Projection Distance:	3.93' to 39.3' (1.2 to 12 m)
Noise Level (STD/Bright):	29dB/31dB
Remote Control:	Fully Featured Remote with Laser Pointer and Mouse Functions
Computer Compatibility:	UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized, VESA, PC and Macintosh Compatible
Video Compatibility:	NTSC, PAL, SECAM, SDTV (480i), EDTV (480p), HDTV (720p, 1080i/p)
Aspect Ratio:	4:3 Native, 16:9 & 16:10 Compatible
Projection Lens:	F=2.4-2.55, f=21.8-24 mm, 1.1x Zoom & Focus
Offset:	115%
Loop Through:	Monitor: D-Sub 15-Pin VGA Output Audio: Stereo Mini-Jack Output (Functional in Both Normal and Standby Modes)
User Controls:	Complete On-Screen Menu Adjustments in 23 Languages
Audio:	Two 5-Watt Stereo Speakers
Keystone Correction:	± 40° Vertical
Vertical Refresh Rate:	25 to 85 Hz
Horizontal Scan Rate:	15.3 to 91.1 KHz
Power Supply:	AC Input 100-240V, 50-60 Hz, Auto-Switching
Power Consumption:	328 Watts (Bright), 272 Watts (STD) <1 Watt (Standby)
Weight:	6.4 lbs (2.9 kg)
Dimensions (W x H x D):	12.76" x 3.82" x 9.21" (324 x 97 x 234 mm)
Operating Temperature:	41° to 104°F (5° to 40°C), 80% Max Humidity, Adjustable Fan Speed for High Altitude Application
Displayable Colors:	1.07 Billion
Projection Method:	Front, Rear, Ceiling Mount, Table Top
Uniformity:	85%
Security:	Kensington® Lock, Keypad Lock and Security Bar
I/O Connectors:	HDMI, Two VGA-In, VGA-Out, S-Video, Composite Video, Three Stereo Audio-In, Stereo Audio-Out, +12V Trigger, USB, RS-232 and RJ45
Standard Accessories:	AC Power Cord, VGA to VGA Cable, Remote Control, Batteries for Remote, USB Cable, Carrying Case, Lens Cap, Quick Start Card, CD-ROM User's Manual and Warranty Card
Optional Accessories:	Wireless Dongle, Ceiling Mount, HDMI Cable, VGA to Component Cable, S-Video Cable, Composite Video Cable, RS-232 Cable and Panoview™ Series Screens
Warranty:	Three Years Optoma Express Replacement Service, One Year on Lamp
UPC:	796435 41 130 5

[www.optoma.com](http://www.optoma.com)

