



Key Features

- Bright at 5000 ANSI lumens with high contrast ratio of 3000:1 (Full On/Off)
- Crestron RoomView® for projector management and control via RJ45 connection
- Presentation-friendly IR remote with USB mouse function and laser pointer
- Environment-friendly design – Consumes <1 Watt in standby mode
- Built-in closed captioning



The Optoma TX779P-3D DLP projector, exceptionally bright at 5000 lumens and 3D capable, provides outstanding video and data display in large rooms and in rooms with high ambient light. Remotely monitor, manage and control the Optoma TX779P-3D over the network via the integrated RJ45 Crestron RoomView® user-friendly interface. The environmentally-friendly TX779P-3D incorporates energy-saving features including <1 watt standby mode, saving you money.

Detail Specifications

Display Technology Single 0.7" DC3 DLP Technology by Texas Instruments	Image Size (Diagonal) 23.4" to 300" (0.59 to 7.62m)	120Hz Frame Sequential 3D for Resolutions Up to 720p, 60Hz Field Sequential 3D for Resolutions Up to 480i
Resolution XGA (1024 x 768)	Remote Control IR Remote Mouse with Laser Pointer	Uniformity 85%
Maximum Resolution UXGA (1600 x 1200)	Keystone Correction ±30° Vertical	Projection Lens F=2.6-2.81, f=26.9-29.8mm, 1.15x Manual Zoom and Focus
Brightness 5000 ANSI Lumens	Displayable Colors 1.07 Billion	Monitor Loop Through D-Sub 15-Pin VGA Output (Functional in Both Normal and Standby Modes)
Contrast Ratio 3000:1 (Full On/Full Off)	Offset 112%	User Controls Complete On-Screen Menu Adjustments in 23 Languages
Lamp Life and Type 3000/2000 Hours (STD/Bright) 300W P-VIP	Computer Compatibility UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized, VESA, PC and Macintosh Compatible	I/O Connectors HDMI, Two VGA-In, VGA-Out, DVI-D, S-Video, Composite Video, Stereo RCA Audio-In, Stereo Audio-In, Stereo Audio-Out, RS-232, USB, RJ45 and 12V trigger
Throw Ratio 1.8 to 2.1:1 (Distance/Width)	Video File Compatibility NTSC, PAL, SECAM, SDTV (480i), EDTV (480p), HDTV (720p, 1080i/p)	Security Kensington® Lock Port and Keypad Lock
Projection Distance 3.28' to 39.4' (1.0 to 12m)	3D Compatibility	

Projection Method

Front, Rear, Ceiling Mount,
Table Top

UPC

796435 41 695 9

Weight

7.8 lbs (3.53kg)

Accessory Part Numbers

Lamp:BL-FS300C
Mount:BM-5001U
Remote:BR-5033L
Case:BK-4013

Dimensions (W x H x D)

12.8" x 4.29" x 10.19" (326 x
109 x 259 mm)

Audio

3-Watt Speaker

Noise Level

28dB/30dB

Horizontal Scan Rate

15, 31 - 90 KHz

Vertical Refresh Rate

50 - 85, 120 Hz

Operating Temperature

41 to 104°F (5 to 40°C), 85%
Max Humidity

Power Supply

AC Input 100-240V, 50-60Hz,
Auto-Switching

Power Consumption

380 Watts (Bright), 320 Watts
(STD), <1 Watt (Standby)

Standard Accessories

AC Power Cord, VGA to VGA
Cable, Remote Control,
Batteries for Remote, Carrying
Case, Lens Cap, Multilingual
CD-ROM User's Manual, Quick
Start Card and Warranty Card

Optional Accessories

HDMI Cable, Ceiling Mount,
VGA to Component Cable,
S-Video Cable, Composite
Video Cable, RS-232 Cable and
Panoview™ Series Screens

Warranty

3-Year Optoma Express
Replacement Service, 1-Year
Lamp