

TX783 – Multimedia Projector

Dazzling and Intense Meets Flexible and Capable

Combining high performance and brightness, the Optoma TX783 has almost limitless install possibilities to achieve perfect images from a distance. Incorporating a center lens design, motorized lens shift and power focus plus extensive connectivity and networking, the flexible and powerful TX783 is ideal for conference facilities and large auditoriums. The latest BrilliantColor™ and scaling technologies plus a DarkChip3™ DLP® chipset from Texas Instruments allow the Optoma TX783 to deliver powerful and vivid images.

Features

- Stunning brightness at 5000 ANSI lumens with 3000/2000 hours (STD/Bright) of lamp life
- Power zoom, focus and lens shift provide installation flexibility
- Professional installation-based DarkChip3 DLP projector with XGA resolution
- Optional wireless connectivity provides both a link for data and video
- Powerful and convenient complete network management through RJ45 connection
- Extensive connections including: HDMI, DVI w/HDCP, two VGA-in, BNC (RGBHV) connectors, S-Video, Composite, RS-232, RJ45, USB mouse control, six audio-in, audio-out, VGA-out, and a 12V Trigger

Specifications

Display Technology

Single 0.7" DarkChip3 DMD
 DLP Technology by Texas Instruments

Resolution

Native XGA (1024 x 768)

Maximum Resolution

UXGA (1600 x 1200)

Brightness (Typical)

5000 ANSI Lumens

Contrast Ratio

1200:1 (Full On/Full Off)

Lamp Life and Type

3000/2000 Hours (STD/Bright)
 350W UHP

Throw Ratio

2.0-2.4:1 (Distance/Width)

Projection Distance

3.9' to 39.4' (1.2 to 12m)

Image Size (Diagonal)

24.4" to 295.5" (0.62 to 7.51m)

Aspect Ratio

4:3 Native, 16:9 and 16:10
 Compatible

Remote Control

Fully Featured Remote Control
 w/ Mouse and Laser Pointer

Audio

Two 5-Watt Speakers

Displayable Colors

134.2 million

User Controls

Complete On Screen Menu
 Adjustments in 21 Languages

Computer Compatibility

UXGA, SXGA+, XGA, SVGA, VGA, VESA, PC
 and Macintosh Compatible

Video Compatibility

NTSC, PAL, SECAM, SDTV (480i), EDTV
 (480p), HDTV (720p, 1080i/p)

Monitor Loop Through

D-Sub 15-Pin VGA Output (Functional in
 Both Normal and Standby Modes)

Lens Shift (Powered)

Vertical $\pm 110\%$ Offset ($\pm 60\%$ Image Height)
 Horizontal $\pm 75\%$ Offset ($\pm 25\%$ Image Width)

Projection Lens

F = 2.0-2.16, f = 28.5-34.1 mm, 1.2x
 Motorized Zoom and Focus

I/O Connectors

HDMI (Audio Supported), DVI-D w/HDCP,
 Two VGA-In, VGA-Out, S-Video, Composite
 Video, Five BNC (RGBHV/YPbPr), Six
 Mini-Jack Audio-In, Audio-Out, USB,
 RS-232, RJ45, +12V Trigger

Security

Kensington Lock Port, Password Protection

Projection Method

Front, Rear, Ceiling Mount, Table Top

Weight

21 lbs (9.5kg)

Dimensions (W x H x D)

15.7" x 6.6" x 18.7" (398 x 167 x 475 mm)

Noise Level (STD/Bright)

30dB/32dB

Horizontal Scan Rate

15 to 100 KHz

Vertical Refresh Rate

43 to 87 Hz

Keystone Correction

$\pm 40^\circ$ Vertical, $\pm 15^\circ$ Horizontal

Uniformity

85%

Operating Temperature

41° to 95°F (5° to 35°C), 80% Max
 Humidity, Adjustable Fan Speed
 for High Altitude Application

Power Supply

AC Input 100-240V,
 Auto-Switching

Power Consumption

410 Watts (Maximum),
 <5 Watts (Standby)

Standard Accessories

AC Power Cord, VGA to VGA
 Cable, USB Cable, RS-232 Cable,
 Remote Control, Batteries for
 Remote, Lens Cap, Quick Start
 Card, CD-ROM User's Manual
 and Warranty Card

Optional Accessories

Wireless Module, Composite
 Video Cable, S-Video Cable,
 HDMI Cable, DVI Cable,
 Audio-Out Adapter and
 Panoview Series Screens

Warranty

3 Years Optoma Express
 Replacement Service, 1 Year on
 Lamp

UPC

796435 11 670 5

Accessory Part Numbers

Lamp: BL-FP350A
 Remote: BR-5019L
 Wireless Module: BI-INTGA

