PLUS

V-807 | V-1100Z

PLUS INTRODUCES THE FIRST PROJECTORS EVER TO WEIGH ONLY

TWO POUNDS. THE V-SERIES "MICRO" PROJECTORS MAY BE

SMALL, BUT THEY ARE MIGHTY POWERFUL. WITH UP TO 1,000

LUMENS AND A CHOICE OF EITHER SVGA OR XGA CLARITY, TO NEW

FEATURES LIKE PICTURE–IN–PICTURE AND HDTV COMPATIBILITY, THEY

ARE THE MOST IDEAL PROJECTORS TO TAKE ANYWHERE.

Ultraportable
at just 2 lbs.

Up to 1,000 ANSI lumens
corner-to-corner brightness

Manual Zoom and Focus

Digital zoom instantly targets and
enlarges the fine print at the touch of
a button

Connects to virtually any computer
or video source

Four-way digital keystone correction

Wireless remote control and built-in
control panel

Picture-In-Picture (PIP)

HDTV compatible

Digital Visual Interface (DVI)

PLUS Vision Corp.

Touchboards

205 Westwood Ave, Long Branch, NJ 07740
Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com

PLUS

V-807 | V-1100Z

Specifications	V-807	V-1100Z
Resolution	SVGA, 800 x 600 pixels	XGA, 1024 x 768 pixels
	SVGA (true)	XGA (true)
	XGA (compressed)	SXGA (compressed)
	VGA (expansion/true)	SVGA/VGA (expansion/true)
Brightness	800 ANSI lumens	1,000 ANSI lumens
Contrast Ratio	800:1 (Full on/off)	2000:1 (Full on/off)
Aspect Ratio	4:3, supports 16:9	4:3, supports 16:9
Projection Lens	F=2.4, f=23 mm	F=2.6-2.9 f=27.5-33 mm
	Manual focus	1:1.2 Manual Zoom/Focus
Digital Keystone Correction	30 degrees, 4-way	30 degrees, 4-way
Digital Zoom	10x	10x
Light Resource	120-watt lamp, 1,000 hr.	120-watt lamp, 1,000 hr.
Color Palette	16.7 million colors	16.7 million colors
Projection Positions	Front, rear, table	Front, rear, table
Projection Distance	3.9-21.6 ft./1.2-6.6 m	3.9-25 ft./1.2-7.9 m
Image Size	36"-200" diagonal/.91-5.08 m	26"-200" diagonal/.66-5.08 m
Video Signal	NTSC, NTSC4.43, PAL, PAL-M,	NTSC, NTSC4.43, PAL, PAL-M,
	PAL-N, PAL60, SECAM,	PAL-N, PAL60, SECAM,
	YCbCr (NTSC, PAL),	YCbCr (NTSC, PAL),
	YPbPr (480p, 720p, 1080i)	YPbPr (480p, 720p, 1080i)
Audio	Mono 0.5 watt	Mono 0.5 watt
Dimensions Excluding Lens and Stand:		
Height	1.8 in./45 mm	1.8 in./45 mm
Width	7 in./180 mm	7 in./180 mm
Length	5.6 in./141 mm	6.5 in./165 mm
Weight	2 lb./0.9 kg	2.2 lb./1.1 kg

Included accessories:
- Wireless remote control
- Power cable (5.9 ft./1.8 m)
- VGA cable (6.6 ft./2 m)
- S-video cable (5 ft./1.5 m)
- Audio cable (5 ft./1.5 m)
- Video cable (5 ft./1.5 m)
- DVI to VGA adapter
- Soft carrying case
- User's manual

Optional accessories:
- ATA shipping cases
- VGA cables (6 ft., 9 ft., 12 ft.)
- Serial mouse cables (6 ft., 9 ft., 12 ft.)
- DVI-D cable (6.6 ft./2 m)
- 3.5 mm, 4-pole plug to RCA component cable (5 ft./1.5 m)
- 15-pin to RCA component cable (10 ft./3 m)
- AverEPack 300 – laptop-free presentation system
- Display-to-Go – output DVI from any laptop

Presentation Screens
Choose from a variety of portable presentation screens from PLUS. They will save the day in any presentation environment.

Replacement Bulbs
PLUS offers a wide array of replacement bulbs so you can carry a spare anywhere.

Remote Controls
Choose from a variety of wireless remotes to fit any presentation environment.

PICTURE BY
DLP™
A TEXAS INSTRUMENTS TECHNOLOGY