















Attachment	Description	Capacity	
Small Pin Grips FG-M6PIN05 FG-M6PIN1 FG-M6PIN2	Ideal for gripping fine wires and filaments; three ranges for checking samples of .02", .04", .08" (0.5, 1 and 2 mm) thick.	22 lb (11 kg)	
Fine Point Grips FG-M6FPG3 FG-M6FPG8	Perfect for testing fine and medium gauge wire, ribbon, tape and paper. Two jaw widths and load capacities are available; both can handle material thickness up to .04" (1 mm).	30 lb (15 kg) .12" (3 mm) 60 lb (30 kg) .31" (8 mm)	
Film Grips FG-M6FLM20 FG-M6FLM50U	These heavy-duty, spring-loaded grips have serrated jaws for handling samples up to .39" (10 mm) thick and .79" (20 mm) or 1.97" (50 mm) wide.	100 lb (50 kg)	
Jacob's Chuck Grips FG-M6JAC5U	Designed for testing low gauge wire and rigid rods; accepts material diameters from .02" (.05 mm) to .20" (5 mm).	100 lb (50 kg)	
Flat Chuck Tensile Grips FG-M6FTG20U	Each serrated gripping face is .79" (20 mm) square and can accept samples up to .79" (20 mm) thick.	100 lb (50 kg)	
Spool Grips FG-M6SP010U	Ideal for hard-to-hold items like thread, filaments, etc. The sample is wrapped around the spool, anchored by friction.	100 lb (50 kg)	
Tape Grips FG-M6TAP30U	Self-tightening lever action makes this fixture perfect for testing rubber, tape and paper.	100 lb (50 kg)	
Wedge Grips FG-M6WDG50U	Two capacities for lighter and heavier loads; spring-loaded jaws automatically close on the specimen and tighten as tension is applied. Ideal for testing wires, strip material and plastic tape or films.	100 lb (50 kg) 500 lb (250 kg)	
Heavy-Duty Tensile Grip FG-M10TEN7U FG-TEN7B	Manually tightened jaw faces can accept samples 1.25" (31.75 mm) wide and .25" (6.35 mm) thick. Contact faces are serrated hardened tool steel.	500 lb (250 kg)	
Clevis Grips FG-M10CLV10U FG-CLV10B	Odd shaped parts, punched samples or tension springs are easily secured and tested. Concave shape to pins assures centering under load. Throat clearance with pin is .5" (12.7 mm) and can easily accept samples up to .375" (9.65 mm) wide.	500 lb (250 kg)	
Cord and Twine Grips FG-M10TWN500U FG-TWN500B	A unique figure 8 wrap of specimen assures a center break and non-locking pins permit quick installation and release. Throat and pin clearance is .375" (9.65 mm) wide with the throat width being .5" (12.7 mm).	500 lb (250 kg)	
Fabric Grips FG-M10FAB80U FG-FAB80B	Eccentrically mounted, serrated roller grips allow for self-tightening of specimens up to 3" (76.20 mm) wide and .25" (6.4 mm) thick.	500 lb (250 kg)	
Adhesive Test Plates FG-M10ADHE3	Samples up to 3" (76.20 mm) in diameter can be tested with hardened tool steel detachable faceplates. Ball socket mounting screws in both grips assure parallelism and perpendicularity to force when load is applied.	500 lb (250 kg)	
Wire Terminal Test Fixture FG-M6WTER100	Designed specifically to test the strength of wire/terminal connections. The upper grip consists of a self-aligning wheel with nine equally spaced slots of various terminal shank sizes; an eccentrically mounted, self-tightening bottom grip secures the wire on the other end.	100 lb (50 kg)	
Compression Plates	Hardened compression plates available - contact distributor regarding part number and pricing.	100 lb (50 kg) 500 lb (25 kg)	