



CARTRIDGE SPECIFICATIONS

Display	160 X 160 touch screen
Connector	Standard DB9 male connector
ESD Protection	± 10kV
Max Software Speed	57.6Kbps
Typical power consumption	2mA Power consumption off
On board Buffer	128 bytes
Data Length	5,6,7,8
Stop bits	1,1.5,2
Parity	none,even,odd,one,zero
Flow Control	Hardware / Software
RS232 Pin Support	TXD,RXD,CTS,RTS,DTR,DSR,RI,CE,GND

SOFTWARE SPECIFICATIONS

Max measurements per variable	2000
Significant digits per measurement	6
Range of Measurement	±20000
Max measurement on 2MB Visor	50000
Max variables per part	100
Max identifiers per part	9
Max parts	100
Max RS232 setups	100
Force Measurement	oz,g,kg,N,lb
Communications	HotSync®
Operation Modes	Peak, average, single readings
PDA	Visor Handspring™ and others
PC Output	Time, Date, Folder, Force reading, Unit
RS232 Setup Option	Allows user to use cartridge with their NON-SHIMPO products

Compatible with: Shimpo FGV, DFS, & DRI digital force gauge series. Can be used with other metrology products which have RS232 output option.

DISTRIBUTED BY: