

TECHNICAL SPECIFICATIONS

HDX-100 Specifications	
Function/Model	HDX-100
VIDEO INPUT	
Bandwidth	1.65Gps
Connector	HDMI Connector x1
HDMI OUTPUT DISPLAY	
HDMI Connector	x 1
RJ45 Jack	x 1
Max. Resolution	1920 x 1200 or 480p/720i/720p/1080i/1080p
Bandwidth	1.65Gps
Storage Temperature	-20°C~60°C
Power adaptor	PS5VDC1A
Housing	Metal
Dimension(mm)	2.75"W x 3.875"L x 1"H

© Copyright 2010 Smart-AVI, All Rights Reserved

Notice

The information contained in this document is subject to change without notice. Smart-AVI makes no warranty of any kind with regard to this material, including but not limited to, implied warranties of merchantability and fitness for any particular purpose.

Smart-AVI will not be liable for errors contained herein or for incidental or consequential damages in connection with the furnishing, performance or use of this material.

No part of this document may be photocopied, reproduced or translated into another language with out prior written consent from Smart-AVI.

Touchboards
205 Westwood Ave, Long Branch, NJ 07740
Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com

Smart-AVI
SMART AUDIO VIDEO INNOVATION

User Manual

HDX-100

HDMI Extender over CAT6 STP



HDMI Extender

Smart-AVI

INTRODUCTION

The HDMI signal transmission unit is placed near the HDMI source. Connect the HDMI source to the transmission unit, which will extend the signal up to 150 feet over a single CAT6 STP cable.

FEATURES

- Compact Transmitter/Receiver Units
- Local HDMI Output
- Perfect Image Quality at all Resolutions (1920 x 1200, 480p, 720i, 720p, 1080i, 1080p)
- Video Resolutions up to 1920 x 1200 at 60H (1280 x 1024 at 75Hz) on all Distances to the Maximum Limit
- Bandwidth to 1.65Gps
- Unit Operates Regardless of Local Monitor Connectivity
- Distances up to 150 Feet using CAT6 STP Cabling
- Compatible with all Operating Systems
- Plug-and-Play – No Software Required


WHAT'S IN THE BOX?

Please check the contents of the package before beginning installation.

Qty	Description	Part Number
1	HDX Transmitter, HDMI over CAT6 STP Cable	HDX-TX100
1	HDX Receiver, HDMI over CAT6 STP Cable	HDX-RX100
1	PowerSupply5V1A	PS5VD3AUS

HDX-100

Connection Diagram



INSTALLATION AND OPERATION

Connecting the Splitter/Extender:

1. Connect the HDX-100 to the Component/TV/Monitor with HDMI cable (included with the unit).
2. Connect HDX-TX100 to HDX-RX100 via CAT6 STP.
3. Connect HDX-RX100 to display.
4. Connect the power.

