

# 715K3 High CO & NOX Analyzer Kit

Designed for use in the oil and gas industry.

Tune compressor engines.



4.0"w x 8.12"h x 2.25"d



Œ

### 1. Combustion Efficiency Analyzer

- Measure 02, CO, and NO
- · Calculate CO2, NOX, efficiency, excess and air ratio
- Designed for combustion engines, tune compressor engines,

### 2. NO & NOX Analyzer

- Measure 0 ~ 5,000ppm NO
- Calculate 0 ~ 5,250ppm NOX

### 3. CO Analyzer

• Measure 0-10% CO

### 4. Differential Thermometer

• Dual input K-type thermocouple temperature tester

### 715 FEATURES

- Easy to use
- Large, easy-to-use display
- Print real-time or stored readings,
   Save 10 sets of data
- 12V car power adapter
- IR printer port
- Protective rubber boot included

selecting oil as fuel be sure to use the optional oil filter or reading could become erratic. Order item A773.

# The Value Leader™

Turn over for technical information and accessory part numbers.

### 715K3 Kit Includes

# STANDARD ACCESSORIES PART # Stainless Steel Hose w/ Fittings ... A607 715 High CO Analyzer ... 715 Flue Temperature Probe w/ K-Type ... A742 K-Type Temperature Probe ... GK11M In-Line Filter Complete ... A762 Mini Pump Protection Filter Assembly ... A763 Rubber Boot ... A765 Soft Carrying Case ... A768 Exhaust Spigot ... A764 Infrared Printer ... A740 Flow Regulator ... A784

# A740 Infrared Printer

- · Easy to use
- Battery operated
- · Self test facility
- Adjustable contrast
- · Manual paper feed
- Maximum

transmitting distance 16"(45cm)

 Compatible with most other combustion analyzers







### **Test Products** International, Inc.

Headquarters: 9615 SW Allen Blvd. Beaverton, OR 97005 USA

503-520-9197 Fax: 503-520-1225 email:

info@tpi-thevalueleader.com

### **Test Products** International, Ltd. 342 Bronte St. South

Unit 9 Milton, Ontario L9T

5B7 Canada

905-693-8558 Fax: 905-693-0888 email:

info@tpicanada.com

### **Test Products** International UK Ltd.

Longley House, East Park Crawley, West Sussex RH10 6AP England Tel: +44 (0)1293 561212 Fax: +44 (0)1293813465

contactus@tpieurope.com

## 715K3 HIGH CO & NOX ANALYZER KIT

Temperature Measurement		
Range	-58° to 1832°F, or -50° to 1,000°C	
Resolution	1°F or °C	
Accuracy (K-type)	±0.3% of Full Scale	

### Nitric Oxide Measurement 0 to 5,000ppm Range Resolution 1ppm <100ppm: ±5ppm Accuracy <1000ppm ±5% >1000ppm: ±10%

NOX Measurement	
Range	0 to 5,250
Resolution	1ppm
Accuracy	Calculated (Specs same as NO)

Gross/Net Efficiency	1	
Range	0 to 100%	
Resolution	0.1%	
Accuracy	Calculated	

Oxygen (0 <sub>2</sub> ) Measu	rement	
Range	0 to 25%	
Resolution	0.1%	
Accuracy	±0.3%	

Carbon Monoxide (CO) Measurement	
Range	0 to 9.999%
Resolution	0.001%
Accuracy	<1.0% CO: ±5% + 5 digits
	<5.0% CO: ±7% + 5 digits
	>5.0% CO: ±10% + 5 digits

Carbon Dioxide (CO <sub>2</sub> )	
Range	0 to 25%
Resolution	0.1%
Accuracy	Calculated
•	

CO/CO2 Ratio		
Range	0 to 0.9999	
Resolution	0.0001	
Accuracy	Calculated	

Instrument Specifications	
Operating Temperature Range	14° to 122°F (-10° to 50°C)
Battery	3AA Batteries
Fuels	Natural Gas, LPG, Light Oil, Heavy Oil
Display	Backlit LCD
Data Storage	10 sets of readings
Time & Date	24 Hour Real Time Clock
Dimensions	200mm x 90mm x 60mm
Weight	500g
Switch Off	Failsafe
Exhaust	Safety Spigot
Conforms To:	BS7927 (and the draft BS7967

ACCESSORIES		
Standard		
Stainless Steel Hose with Fittings	A607	
Flue Temperature Probe w/K-type	A742	
K-Type Temperature Probe	GK11M	
In-Line Filter Complete	A762	
Mini Pump Protection Filter Assembly	A763	
Rubber Boot	A765	
Soft Carrying Case	A768	
Exhaust Spigot	A764	
Optional		
Infrared Printer	A740	

NOTE: When selecting oil as fuel be sure to use the optional oil filter or reading could become erratic. Order item A773.



To learn about the entire line of TPI products visit: