



775 Combination Carbon Monoxide & Combustion Gas Leak Detector

**New!
Two Tools
in One!**

The TPI 775 is a state-of-the-art Carbon Monoxide and Combustible Gas Leak Detector. It is the first of its kind to combine both detection technologies into one easy to use hand-held affordable instrument.



The TPI 775 is a state-of-the-art Carbon Monoxide and Combustible Gas Leak Detector. It is the first of its kind to combine both detection technologies into one easy to use hand-held and affordable instrument.

- Easy to use
- One hand operation
- Auto zero
- Back light
- Visible and audible alarm

Turn over for technical information and accessory part numbers.

The Value Leader™

Sensor Specifications

Type	Resolution	Range	Accuracy
Leak	<50ppm	0-50,000ppm	±10%
CO	1ppm	0-2,000ppm	±5ppm or 5%; whichever is greater



TECHNICAL SPECIFICATIONS AND ACCESSORIES

- Digital Multimeters
- Clamp Meters
- Hand-held Oscilloscopes
- Refrigerant & Combustible Gas Leak Detectors
- Temperature Testers
- BNC Coax Cable Connectors
- Test Leads
- Accessories

Test Products International, Inc.

Headquarters:
9615 SW Allen Blvd.
Beaverton, OR 97005
USA
503-520-9197
Fax: 503-520-1225
email:
info@tpi-thevalueleader.com

Test Products International, Ltd.

342 Bronte St. South
Unit 9
Milton, Ontario L9T
5B7
Canada
905-693-8558
Fax: 905-693-0888
email:
info@tpicanada.com

Test Products International UK Ltd.

Longley House, East Park
Crawley, West Sussex
RH10 6AP England
Tel: +44 (0)1293 561212
Fax: +44 (0)1293813465
contactus@tpieurope.com

775 Combustion Carbon Monoxide & Combustion Gas Leak Detector

SPECIFICATIONS

Alarms	Visual and Audible
Response Time:	
CO	90% in 30 seconds
Leak	Instantaneous
Goose Neck Length	16" (406mm)
Dimensions	9.5" x 2.9" x 2.2" (240mm x 74mm x 55mm)
Power	2C Alkaline Batteries
Power Consumption	About 400mW in typical use
Operating and Storage Temperature	32° to 120°F (0° to 50°C)
Warranty	3 years
Standard Accessories	Soft Carrying Case Manual 2C Alkaline Batteries
Optional Accessories	Earphones

SENSOR SPECIFICATIONS

Type	Resolution	Range	Accuracy
Leak	<50ppm	0-50,000ppm	±10%
CO	1ppm	0-2,000ppm	±5ppm or 5%; whichever is greater



To learn about the entire line of TPI products visit:

www.tpi-thevalueleader.com

L 775-0604

Copyright © 2004 Test Products International, Inc.