

Handheld Infrared Transmitter/Mic IRH-35



Handheld infrared microphone/transmitter with NiMH batteries

Specifications

Transmission Carrier	Infrared
Transmission Frequencies	2.08 MHz & 2.54 MHz
2 Channel Switchable	Field Switchable
Transmitting Diodes	Ten
Modulation	FM Wide-Band
Pilotone Frequency	32.768 KHz
Peak Deviation	± 25KHz
Operating Range	2500 Ft ² . 60 Ft.
Power Switch (Slide)	On/Off
Battery Charge Level (LED)	Green (Useable Charge) Red (Needs Charging)
Battery Life	Approx. 7 Hr./Charge
Dimensions	2 1/8" Dia. Head, 1 7/16" Dia. Body, 9 5/8" H
Weight	10.3 oz. w/ Battery

Features

- Condenser microphone element
- Power "on/off" switch
- Battery level indicator—LED
- Channel "A" or "B" selectable
- 10 high-power emitting diodes
- Diodes at top and bottom of handle for increased Coverage (2 Top aimed out, 6 Bottom 360°, 2 Bottom aimed down)
- 360° IR radiation for assured connectivity
- Two "AA", Duracell, rechargeable NiMH batteries

Touchboards

205 Westwood Ave, Long Branch, NJ 07740
Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com

TeachLogic, Inc. 1688 Ord Way Oceanside, CA 92056

☎ 800-588-0018

TeachLogic
FOR SOUND LEARNING