

Titan Portable PA-700



Titan AC/Battery powered portable sound system (basic unit). The Input Panel provides a Lo-z XLR Microphone Input with Volume Control, Stereo Line Input with volume control and Dual Line Output, Treble & Bass Controls, Master Volume Control. Voice Priority Button with LED.

Specifications

Output Power	50 W RMS, 80 W Max
Sensitivity	95 dB, 1W @ 1 M
Maximum SPL	122 dB
Frequency Response	20 Hz–20 kHz (audio)
Speaker	8" LF Woofer, 1" HF Horn
Signal to Noise Ratio	>70dB
Audio Input	XLR-TRS Balanced Mic Line Level, Dual RCA
Audio Output	Line Level, Dual RCA
Controls	Master Volume, Treble, Bass, Mic Vol., Voice Priority Button
Rechargeable Battery Type	Two 12 VDC / 2.7 AH
Operating Life	About 4–6 hours
Charging Time	About 6–8 hours
Power Supply	100–240 V AC Input European Approval
Dimensions	11 ¾" W x 18 ½" H x 9" D
Weight	25 lbs.

Features

- Durable high impact enclosure
- Efficient two-way speaker system
- Simultaneous mixing with the microphone inputs
- Plug-In microphone, Lo-z, XLR Connection
- Treble and bass controls
- Dual line input and output (RCA)
- Rechargeable sealed lead-acid batteries for an extended 4-6 hours of continuous use
- AC Operable without batteries being fully charged — AirLink transmitter for wireless transmission of program to powered companion speaker
- Voice Priority Button
- Can be upgraded to include up to two Wireless Receiver, Wireless Transmitter & CD/MP3 Player
- AirLink Router and Spartan compatible