testo 206-pH2

The pH measuring instrument for spot checks on semi-solid food, e.g. jelly, cream, meat, cheese, fruit...

The protection case included "TopSafe" (IP 68) is waterproof, hygienic and dishwasher-safe.

testo 206-pH2 instrument set: One-hand pH/°C measuring instrument, pH2 probe head for semi-solid substances, storage cap with gel, TopSafe and belt/wall holder

Part no.

0563 2062

Compact pH tester - For semi-solid food

- pH2 probe head for semi-solid food
- Leak-proof storage gel
- Used for food containing protein
- Combination: pH penetration tip with temperature measurement probe
- Automatic full-scale recognition



Easy exchange of probes with testo 205, testo 206-pH1/-pH2/-pH3





pH2 probe head for semi-solid food

Set	Part no.
testo 206-pH2 Starter Set: One-hand pH/°C measuring instrument, pH2 prol substances, storage cap with gel, calibration dosi TopSafe, belt/wall holder and aluminium case	

Accessories	Part no.
Additional accessories and spare parts	
Spare pH probe pH2 for testo 206 incl. gel storage cap	0650 2062
Storage cap for testo 206 with KCI gel filling	0554 2067
Storage cap for testo 206 with KCl gel filling (pack of 3)	0554 2068
Replacement Li-battery button cell type CR 2032	0515 0028
pH buffer solution 4.01 in dosing bottle (250 ml) with DKD calibration certificate	0554 2061
pH buffer solution 4.01 in dosing bottle (3 x 250 ml per pack) with DKD calibration certificate	0554 2062
pH buffer solution 7.00 in dosing bottle (250 ml) with DKD calibration certificate	0554 2063
pH buffer solution 7.00 in dosing bottle (3 x 250 ml per pack) with DKD calibration certificate	0554 2064
pH buffer solution 10.01 in dosing bottle (250 ml) with DKD calibration certificate	0554 2065
pH buffer solution 10.01 in dosing bottle (3 x 250 ml per pack) with DKD calibration certificate	0554 2066





205 Westwood Ave Long Branch, NJ 07740 1-877-742-TEST (8378) Fax: (732) 222-7088 salesteam@Tequipment.NET

Technical data			
Probe type	pH electrode / NTC	Oper. temp.	0 to +60 °C
Meas. range	0 to 14 pH 0 to 60 °C (Short-term to +80 °C max. 5 min)	Storage temp.	-20 to +70 °C
		No. meas. channels	2 channel
		Temperature compensation	Automatic
±1 digit ± Resolution C	±0.02 pH ±0.4 °C 0.01 pH 0.1 °C	Meas. rate	2 measurements per second
		Battery type	1x CR2032
		Material/Housing	ABS with TopSafe, Protection type IP 68
		Battery life	80 h (Auto Off 10 min)
		Dimensions	197 x 33 x 20 mm
		Weight	69 g
		Display	LCD, 2 lines

testo 206-pH2 instrument set



One-hand pH/°C measuring instrument, pH2 probe head for semi-solid substances, storage cap with gel, TopSafe and belt/wall holder



One-hand pH/°C measuring instrument, pH2 probe head for semi-solid substances, storage cap with gel, calibration dosing bottles 250 ml pH 4+7, TopSafe, belt/wall holder and aluminium