

Model AD105

True-rms Digital Ammeter



- Broad range 1000 A, AC and DC ammeter
- True-rms
- Peak Hold and DC Auto Zero
- Autoranging
- 4000-count
- Belt-clip sleeve case included
- CAT III 1000 V rated

AD105 Specifications (at 23 °C ± 5 °C, < 80 % R.H. non-condensing)

AC Current (40-400 Hz)

Ranges	400 A, 1000 A
Accuracy	0 - 40 A ± (1.9 % rdg + 8 dgts) 40 - 400 A ± (1.9 % rdg + 7 dgts) 400 - 1000 A ± (2.9 % rdg + 5 dgts)
Crest Factor	(C.F. 1.4 to 2.0) + (1.0 % rgd) (C.F. 2.0 to 2.5) + (2.5 % rgd) (C.F. 2.5 to 3.0) + (4.0 % rgd)

Position Error ± (1.0 % rdg)

Resolution 0.1 A in 400 A range

AC Current (Peak Hold)

Ranges	Low, High
Accuracy	± (3.0 % rdg + 10 dgts)
Resolution	0.1 A in Low range

DC Current

Ranges	400 A, 1000 A
Accuracy	0 - 100 A ± (2.9 % rdg + 8 dgts) 100 - 400 A ± (1.9 % rdg + 5 dgts) 400 - 1000 A ± (2.9 % rdg + 5 dgts)

Position Error ± (1.0 % rdg)

Resolution 0.1 A in 400 A range

Frequency

Ranges	4 kHz, 10 kHz
Accuracy	± (0.5 % rdg + 3 dgts)
Resolution	1 Hz in 4 kHz range
Min. Input Frequency	20 Hz
Sensitivity	< 1 kHz 6 A rms 1 - 10 kHz 10 A rms



General Specifications

Display: 3³/₄ digit LCD (max reading 3999); **Display Update Rate:** 2/sec; **Overrange Indication:** "OL" indicated; **Low Battery Indication:** Battery symbol appears when battery power is low; **Power Supply:** One 9 V battery (NEDA 1604, IEC 6F22); **Battery Life:** Alkaline 40 hours, approx.; **Maximum Jaw Opening:** 51 mm; **Maximum Conductor Size:** 51 mm (2 inches); **Operating Temperature:** 0 °C to +50 °C, < 75 % R.H. non-condensing; **Storage Temperature:** -20 °C to +60 °C, < 80 % R.H. non-condensing, batteries removed; **Temperature Coefficient:** 0.2 x (Spec. Acc'y), < 18 °C or > 28 °C; **Dimensions (WxHxD):** 240 x 106 x 40 mm; **Weight:** 420 g (incl. Battery); **Included Accessories:** Manual, carrying case

Features

True-rms, Hall effect sensor; Auto Power Off: Approx. 30 minutes after no function change; Peak Hold; Warranty: One-year



Model AD105

True-rms Digital Ammeter

Meterman.
The right tool for the job.™

Meterman Test Tools
website: www.metermantesttools.com
email: info@metermantesttools.com

6920 Seaway Blvd.
Everett, WA 98203
fax: 425-446-4882
tel: 877-596-2680

Meterman Test Tools Europe
P.O. Box 1186
5602 BD Eindhoven
The Netherlands

©2002 Meterman Test Tools. All rights reserved.
Printed in U.S.A. 1/2002 1646267 D-ENG-N Rev A