

**NEW**



Power unit WR 2, 300 Watts

**The new WR 2 has been designed to deliver high performance at an affordable price.**

*For rework and repair of printed circuit boards (PCBs).*

If you need a station that will allow you to perform both soldering and desoldering operations at the same time - or soldering and hot air tasks - then the WR 2 is for you. This new rework station from Weller is based on our highly successful WR 3M product range. And with its two channel design, it offers superior performance at an affordable price.

This new station lives up to Weller's high quality reputation. These tools allow operators to work more efficiently both in terms of time and energy as well as helping to extend tip lifetime.

The two channels of the WR 2 power unit allows up to 78 combinations of soldering, desoldering, non-contact hot air, pre-heat, or solder bath functions. Two tools can be operated simultaneously as long as the total power of the two tools does not exceed 300 watts. In addition, to save on power consumption, an ECO function on the unit allows the tools to go into a 'sleep mode' when not in use.

### Ordering Information

Order No.	Description
WR 2	Two Channel Rework Power Unit, 300 W

### Key Features

- Two independent tool channels with automatic tool recognition
- Allows simultaneous use of two tools (maximum of 300 watts)
- Compatible with most Weller soldering and desoldering irons up to 200 watts
- Self contained vacuum and air turbine
- ECO button for "Sleep Mode"
- Programmable temperature memory key
- ESD safe
- Weller Micro-Tools, WMRP & WMRT are not compatible

WR 2 technical details	
Dimensions L x W x H	10.75 x 9.25 x 4.00 in. (273 x 235 x 102 mm)
Weight	6.3 lbs. (2.9 kg.)
Power Supply Voltage	120 VAC, 60 Hz
Power Consumption	300 Watts
EOS / ESD Properties	All Tool Handles, Cords, and Air Flow are Static Free
Fuse	4 Amp
Temperature Range	Variable in (1) degree increments from 150 – 999 F
Temperature Accuracy	+/- 17 F
Temperature Stability	+/- 9 F
Hot Air / Vacuum Pump (duty cycle: 30 seconds on, 30 seconds off)	Maximum vacuum 0.7 bar Max. delivery rate 18 l/min. Hot air max. 15 l/min.

**NEW**



### Available Configurations

Cat. No.	Description
WR2000	Two Channel Digital Rework Station with Non-Contact Hot Air Pencil
Contents:	
WR2	Power Unit, 300W
0052711599	HAP1 100W Hot Air Pencil with 3.0 mm round nozzle
0051515299	WDH 30 Safety Rest
	Power Cable
	Instructions



Cat. No.	Description
WR2000X	Two Channel Digital Rework Station with Desoldering Iron
Contents:	
WR2	Power Unit, 300W
0051318099	DXV 80 80 W Desoldering Iron with DX112 Deslodering Triplet
0051515399	WDH 40 Safety Rest
	Power Cable
	Instructions



Cat. No.	Description
WR2000VX	Two Channel Digital Rework Station with Soldering and Desoldering Irons
Contents:	
WR2	Power Unit, 300W
0052918099	WP 80 80 W Soldering Iron with LTB tip
0051515299	WDH 10T Safety Rest with Stop and Go Function
0051318099	DXV 80 80 W Desoldering Iron with DX112 Deslodering Triplet
0051515399	WDH 40 Safety Rest
	Power Cable
	Instructions

### Available Accessories

Hand Piece	Part # Order # Tip Supplied
	WSP80 0052918099 LTB Tip
	WP80 0052918099 LTB Tip
	WMP NT1 Tip
	WTA50 0051317199 WTA1 Tip
	WSP150 0052917099 LHTF Tip
	WP120 0052919399 XTB Tip
	MPR80 0053313199 LTB Tip
	FE75 0052916699 LTB Tip
	WHP80 0052702899 Hot Plate 3.2" X 2"
	WSB80 0052704099 80 Watt Solder Bath
	WSB150 0052704299 150 Watt Solder Bath
	HAP1 0053311499 100 Watt R04 & R06 Tips
	DXV80 0051318199 DX113 Tip
	DSX80 0051319099 DX113 Tip