

# AVerVision®CP355

Better than Real







## **Clear Image Quality**


3.2-megapixel camera sensor captures vivid images of documents, 3D objects, and live movements.



to 10X.



Accurately place any object under the camera using the patented laser positioning guide.





## **Immediately Grab Attention!**







instructional demonstrations.



## **All-New Revolutionary AVer+ Software**

- · Leverage content from an AVerVision visualizer, a computer, the internet, and user-created material to provide a rich learning experience
- · Organize your teaching material on multiple project pages with unlimited page space for intuitive learning
- · Write, draw, or type text on top of any material you have chosen to use
- · Record and share your favorite teachings and your students' work

### With a visualizer, you can display...



	Computer Frograms
Product Specifications	
Product Specifications	4/0 F" CMOC Color Image Consor
Image Sensor	1/2.5" CMOS Color Image Sensor
Total Pixels	3.2M Pixels
Output Resolution	HD 720p (1280 x 720)
Lens	F 3.2 (Wide), F 6.8 (Tele)
Zoom	80X Total Zoom (10X AVer® Optical Zoom + 8X Digital Zoom)
Frame Rate	24fps (Max.)
Focus	Auto / Manual
Shooting Area	400 x 300mm (Max.)
Image Rotation	Camera Head 0° / 90° / -90°
Image Storage	Built-in Memory (Max: 80; up to 3M each)
On-Screen Display (OSD)	Provided
Image Effects	Color / B&W / Negative / Mirror / Reverse / Freeze
Image Adjustments	Auto / Manual
(White Balance / Exposure / Night View)	
AVerPresenter	Provided (AVerBox & AVerVisor)
Split Screen	Provided (Vertical & Horizontal)
Picture-in-Picture	Provided
Display Mode	Text / Graphics / High Frame / Wide Angle / Macro / Infinite / Microscop
Capture Mode	Single / Continuous
User Profiles	Up to 3
Timer	Provided
Flicker Filter Control	Provided (2 Levels)
Remote Control	Provided (with Laser Pointer)
DVI-I Output	Provided
RGB Input	Provided (15-Pins D-Sub, Pass Through)
RGB Output	Provided (15-Pins D-Sub, Pass Through)
S-Video & Composite Video Output	Provided (NTSC or PAL)
RS-232 Port	Provided (with S-Video / RS-232 Adapter cable)
USB 2.0 Port	Provided (PC Camera / Built-in Image Download)
Light Source	Embedded LED Lamp
Laser Positioning Guide	Provided Provided
Dimension	Operating: 180mm x 430mm x 600mm
Difficuation	Folded: 245mm x 355mm x 63mm
Not Words	
Net Weight	2.6kg (5.73lbs)
Power Consumption	20W (Max.)
Certifications	FCC, CE
Compatible Operating System	
Windows®	XP (SP2), Vista (32-bit or 64-bit)
Macintosh®	OS 10.4 (Tiger), OS 10.5 (Leopard)
Package Content	
AVerVision® CP355 Unit	Remote Control with Batteries
AVer+ Software CD	User Manual CD
Power Adapter	Quick Guide
RGB Cable	Warranty Card
USB Cable	Anti-Glare Sheet
S-Video / RS-232 Adapter Cable	Carrying Bag
T. T. T. T. C. E. C. T. Gaptor Gabio	





With a visualizer, display images











#### **Optional Accessories**







Microscopic Adapter

Light Box

Security Bracket

#### Distributor / Dealer:





