

# CD737x



## BRIGHTNESS

3000 ANSI lumens (boost)  
2700 ANSI lumens (standard)  
2500 ANSI lumens (eco)

## RESOLUTION

1024x768 true XGA  
1280x1024 SXGA compressed

## DISPLAY TYPE

TI DMD 0.7", 12° DDR, DLP chip

## CONTRAST RATIO

2000:1

## ASPECT RATIO

4:3 Native  
16:9 Compatible

## LAMP

200 watt OSRAM VIP

## LAMP LIFE

2000 hours (boost)  
3000 hours (standard)  
4000 hours (eco)



Special features of the CD737x include:

**User friendly lamp replacement**—Top cover access means no need for dismantling the projector to change the lamp.

**Custom start-up screen**—Download a jpeg file to customize your start-up image.

**Three lamp modes**—Change your lamp output for varying light conditions and save on lamp life.

**Multiple inputs**—Connect to multiple peripheral systems at the same time.

**Color management**—Adjust individual colors as needed.

## OPTIONAL ACCESSORIES:

Extended Warranty  
Mac Adapter / DVI Adapter  
Cable: Audio / VGA / Component / Composite Video  
Universal Ceiling Mount / Suspension Pole/ Round Flush Kit  
Spare Lamp Module

## SHIPS WITH:

Laser Remote Control  
User Manual/CD ROM  
Power Cord, Lens Cap & Soft Carry Case  
USB Mouse, S-Video Cable  
DVI/VGA 15 pin Computer Cable

## DIAGONAL IMAGE SIZE

37" - 240" inches

## PROJECTION LENS

Manual zoom/focus

## ZOOM RATIO

1.22:1 Ratio

## THROW DISTANCE

4.9' - 26' feet  
1.5 - 8 meters

## THROW RATIO

1.63 - 2.0 (x screen width)

## INPUTS

Component (R,G,B) Mini audio jack  
Composite Video (R/L audio) S-Video  
DVI - I VGA-in

## OUTPUTS

VGA-out, Mini jack audio

## COMPATIBILITY

VGA, SVGA, XGA, SXGA, Mac

## PROJECTOR CONTROLS

RS232, USB (mouse control)

## KEystone

+/- 15° vertical

## VIDEO

NTSC, NTSC 4.43, PAL,  
SECAM

## HDTV / EDTV / SDTV

480i/p, 576i/p, 720p, 1080i

## AUDIO

1 X 2 watt speakers

## DIMENSIONS (WxDxH)

12.9" x 3.5" x 9.4" inches  
32.8 x 8.8 x 23.8 cm

## WEIGHT

7.8 lbs / 3.55 Kg

## DECIBEL RATING

38 dB (boost) / 36 dB (standard) / 33 dB (eco)

## WARRANTY

3 year parts & labor  
90 day lamp

## FCC CERTIFICATION

Class B

## H-SCAN FREQUENCY

Horizontal—15-70 kHz

## V-REFRESH RATE

Vertical—50-85 kHz

## POWER SUPPLY

110-240 Voltage (auto ranging)

## PWR. CONSUMPTION

260 Watts (boost)  
250 Watts (standard)  
230 Watts (eco)

**BOXLIGHT**<sup>®</sup>  
CORPORATION

19462 Powder Hill Place, Suite 101  
Poulsbo, WA 98370

**Touchboards**

205 Westwood Ave, Long Branch, NJ 07740

Phone: 866-94 BOARDS (26273) / (732)-222-1511

Fax: (732)-222-7088 | E-mail: sales@touchboards.com