

Phoenix X30



BRIGHTNESS

3500 Lumens (Boost)
3000 Lumens (Standard)
2500 Lumens (Eco)

RESOLUTION

1024 x 768 True XGA
1280 x 1024 SXGA Compressed

DISPLAY TYPE

0.7" x 1, 12° DLP

CONTRAST RATIO

2100 :1

LAMP

200 watt OSRAM VIP

LAMP LIFE

2000 Boost
3000 Standard
4000 Eco

ASPECT RATIO

4:3 Compatible 16:9

DIAGONAL IMAGE SIZE

23.4" - 273.4" Inches



Special features of the Phoenix X30 include:

Three lamp modes—Change your lamp output for varying light conditions and save on lamp life.

Password security—Protect use from multiple users or theft.

Fan speed options—Enables better control of the projector's temperature and cooling process.

Top Changing Lamp—When ceiling mounted you can change the projector's lamp with ease

Custom Splash Screen—Customize the start-up screen on the projector.

OPTIONAL ACCESSORIES:

Extended warranty
Mac Adaptor / DVI-D Cable / Audio / VGA / Component / Composite Video
Universal Ceiling Mount / Suspension Pole / RS232 Cable
Round Flush Kit
Security Cable / Spare Lamp Module

SHIPS WITH:

Laser Remote Control with Batteries
Power Cord / USB Cable
Computer Cable
Quick Start Guide / User Manual CD Rom

PROJECTION LENS

Manual Zoom / Focus

THROW DISTANCE

3' - 32' Feet
1 - 10 Meters

THROW RATIO

1.8 ~ 2.1 (x screen width)

ZOOM RATIO

1.15:1

INPUTS

DVI-D / HDCP
VGA-in / Component
S-Video
Composite Video
RCA audio (R/L)
Audio (Mini jack)

OUTPUTS

Audio (Mini jack)
VGA (Out)

COMPATIBILITY

VGA, SVGA, XGA, SXGA, Mac
EDTV / SDTV / HDTV
480i/p / 720p / 1080i

PROJECTOR CONTROLS

RS232

USB

12V Trigger

KEystone

+/- 15° Vertical

DIMENSIONS (WxDxH)

12" x 9.6" x 3.4" Inches
30 x 24.4 x 8.8 cm

WEIGHT

7.3 Lbs / 3.3 Kg

VIDEO COMPATIBILITY

NTSC / NTSC 4.43 / PAL B/G/H/I/M/N 60 / SECAM

AUDIO

1 x 3w Mono Speaker

DECIBEL RATING

36dB (boost) / 33dB (standard) / 31dB (eco)

WARRANTY

3 year parts & labor / 90 day lamp

FCC CERTIFICATION

FCC-B, UL, C-UL, TUV, CB, CE, CCC

H-REFRESH RATE

Horizontal—15-90 kHz

V-REFRESH RATE

Vertical—50-85 kHz

POWER SUPPLY


AC input 110 ~ 240
Voltage (auto ranging)

POWER CONSUMPTION

290W (boost)
255W (standard)
230W (eco)

BOXLIGHT
CORPORATION

19462 Powder Hill Place, Suite 101
Poulsbo, WA 98370



TOUCHBOARDS
1-866-942-6273 .COM

205 Westwood Ave, Long Branch, NJ 07740
Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com

www.boxlight.com
Direct 800.762.5757
International 360.779.7901
Partners 866.688.3636