

# Pro7500DP

## Specifications



<b>BRIGHTNESS</b> 7500 lumens (Standard)	<b>PROJECTION LENS</b> Power Zoom/Focus	<b>OUTPUTS</b> Monitor out (DB-15) x 1 Audio (PC) x 1	<b>LENS SHIFT</b> Powered, Vertical (0-50%) Horizontal (+/-10%)
<b>RESOLUTION</b> 1024 x 768 XGA (Native) 1600 x 1200 UXGA (Supported)	<b>DIAGONAL IMAGE SIZE</b> 40" - 300"	<b>KEYSTONE</b> Horizontal keystone: V (+/-40°) H (+/-35°) @ (TR 1.78), Optical offset 50% under single direction	<b>H-REFRESH RATE</b> 15, 31 - 90 kHz
<b>DISPLAY TYPE</b> Texas Instruments DMD 0.7" x 1 LVDS DLP w/ DDP 3020	<b>THROW DISTANCE</b> 1.7~2.9 (standard lens) 2.0 (wide fixed lens) 1.8~2.3 (wide zoom lens) 2.1~2.9 (long zoom 1 lens) 2.2~3.1 (long zoom 2 lens)	<b>PROJECTOR CONTROLS</b> RJ-45 x 1 USB RS232 (9-pin D-sub) Screen trigger, 3.5mm	<b>V-REFRESH RATE</b> 50 - 85 Hz
<b>COLOR</b> 16.7 million (24-bits/Pixel)	<b>LAMP</b> 280 watts (Standard) dual lamp 230 watts (Economy) dual lamp	<b>PROJECTION METHODS</b> Desktop front/rear; Ceiling front/rear	<b>DECIBEL RATING</b> 31dB (typical)/32dB (max) single 34dB (typical)/35dB (max) single 34dB (typical)/35dB (max) dual 39dB (typical)/40dB (max) dual
<b>CONTRAST RATIO</b> 1000:1 / 2100:1 with DB	<b>LAMP LIFE</b> 2000 Hours (Standard) 3000 Hours (Economy)	<b>COMPATIBILITY</b> VGA, SVGA, XGA, SXGA	<b>POWER SUPPLY</b> 100~240V/AC
<b>ASPECT RATIO</b> 4:3 (Native) 16:9 (Supported)	<b>INPUTS</b> DVI-D (HDCP) x 1 VGA (DB-15) x 1 Component 1 - BNC x 5 Component 2 - RCA x 3 S-Video (mini DIN) x 1 Composite video (RCA x 1) Audio (video) -RCA x 2 (S-Video), RCA x 2 (Component video) Audio (3.5mm) -DVI-Dx1, VGA x 1, 5BNC x 1	<b>EDTV / SDTV / HDTV</b> 480i/p, 720p, 1080i	<b>POWER CONSUMPTION</b> 710w (typical - standard dual) 375w (typical - standard single) 580w (typical - economy dual) 315w (typical - economy single)
<b>THROW RATIO</b> 1.78~2.35 (standard lens) 0.774 (wide fixed lens) 1.33~1.79 (wide zoom lens) 2.22~4.43 (long zoom 1 lens) 4.43~8.3 (long zoom 2 lens)		<b>FCC CERTIFICATION</b> Class B, IECS-003 class B	<b>DIMENSIONS (WxDxH)</b> 20.35" x 15.63" x 7.68" 517 x 397 x 195mm
<b>THROW RATIO</b> 1.32:1 (standard lens) N/A (wide fixed lens) 1.34:1 (wide zoom lens) 2.0:1 (long zoom 1 lens) 1.85:1 (long zoom 2 lens)		<b>VIDEO COMPATIBILITY</b> NTSC, NTSC 4.43, PAL B/G/H/I/M/N/60, SECAM	<b>WEIGHT</b> 46 lbs *without lens 21 Kg
		<b>AUDIO</b> 2 x 3w Stereo Speakers	<b>WARRANTY</b> 3 year parts & labor / 90 day lamp



### Accessories:

- Remote control
- AC power cord
- VGA cable
- Lens cap
- Rubber cap (12V screen control)
- Anti-theft screw for lens
- Owner's Manual CD