

SeattleX30N



BRIGHTNESS

3000 ANSI lumens (standard)
1950 ANSI lumens (eco)

RESOLUTION

1024 x 768 True XGA
1280x1024 SXGA compressed

DISPLAY TYPE

3LCD technology

CONTRAST RATIO

500:1

ASPECT RATIO

4:3 Native
16:9 Compatible

LAMP

230 watt

LAMP LIFE

2000 hours (standard)
3000 hours (eco)

COLOR

16.7 million (24 bit)



Special features of the SeattleX30N include:

LAN Connectivity—For network installation. Manage your projectors through a web-based platform.

Quick Start up and Shut down—Start presenting quickly and only a 10 second cool down cycle when you finish!

Seven Display Modes—Use on a whiteboard, greenboard, blackboard, in daylight, cinema, natural or user set.

Side Changing Lamp and Filter—Easy lamp installation and projector maintenance. No need to remove the projector from ceiling mount position.

OPTIONAL ACCESSORIES:

Replacement lamp
Ceiling Mount / Suspension Pole/ Round Flush Kit
Security Cable
Cables: Mini jack adapter / Composite video / S-Video / Audio
Soft carry case

SHIPS WITH:

Remote control w/ batteries & laser pointer
User Manual (CD-ROM)
Power Cord
USB cable, VGA cable
Quick start guide

DIAGONAL IMAGE SIZE

40" - 300" inches

PROJECTION LENS

Manual zoom & Focus

ZOOM RATIO

1.2 x zoom lens

THROW DISTANCE

3.33' - 25.0' feet

1.01 - 7.62 meters

THROW RATIO

1.45~1.73 (x screen width)

INPUTS

VGA

DVI-I

S-Video

Composite

Component

Audio x 3 (PCI, PC2, Video)

USB Mouse Control

RJ45 LAN Connection

OUTPUTS

VGA Monitor Output

Audio (mini jack)

RJ45 LAN Connection

COMPATIBILITY

VGA, SVGA, XGA, SXGA,

UXGA, Mac

ADJUSTMENTS

On-board & remote

CONTROLS

RS232

RJ45 LAN Connection

H-SCAN FREQUENCY

Horizontal—31-92 kHz

V-REFRESH RATE

Vertical—48-120 kHz

KEystone

+/- 30° Vertical

VIDEO

NTSC, NTSC 4.43, PAL (B/G/
H/I/MN60), SECAM

HDTV / EDTV / SDTV

480i/p, 576i/p, 720p, 1080i

AUDIO

1 x 8 watt speaker

DIMENSIONS (WxDxH)

12.8" x 10.24" x 3.8" inches

32.5 x 26.0 x 9.7 cm

WEIGHT

7.3 lbs / 3.3 Kg

REGULATIONS

FCC-B, UL/cUL, TUV, CD, CE,

CCC

SECURITY

Kensington

Access Password

Security Arm Bar

POWER SUPPLY

Ac 100-240V at 50-60Hz

PWR. CONSUMPTION

312 Watts

<5w standby

SOFT POWER ON/OFF

Yes

DECIBEL RATING

33 dB (standard) / 31 dB

(eco)

WARRANTY

3 year parts & labor



205 Westwood Ave, Long Branch, NJ 07740

Phone: 866-94 BOARDS (26273) / (732)-222-1511

Fax: (732)-222-7088 | E-mail: sales@touchboards.com