

# CASIO®



**TOUCHBOARDS**  
1-866-942-6273 .COM

205 Westwood Ave, Long Branch, NJ 07740  
Phone: 866-94 BOARDS (26273) / (732)-222-1511  
Fax: (732)-222-7088 | E-mail: sales@touchboards.com

## SUPER SLIM PROJECTOR

# XJ-S41

## Travel Light and Super Bright!

**The XJ-S41 is 2500 ANSI LUMENS**



- 2500 Lumens
- Fits in Your Briefcase!
- 2X Optical Zoom
- Native XGA 1024 x 768 Resolution
- Multimedia 1080i Compatible
- Built-in Speaker/Stereo Out
- 3.9 lbs.

### Road Warrior Designed!

Dimensions that are designed to travel with your laptop. Slide it right in to your attaché case.

### 2X Optical Zoom!

Don't be moving the projector all around the room. Large room or small, just zoom to fit your presentation on the screen. 2X zoom gives you one of the largest selections of proper throw distances.

### Vivid Image Color Wheel Technology!

Casio, one of the world's leaders of digital camera technologies, has designed a projected image that looks brighter and has enhanced contrast.

### Projector Selection!

Casio lets you choose the model that is right for your needs. Choose from 4 models that offer brightness selection and optional wireless capability.

### Road Warrior Stylish!

The projector that projects a great image on the screen for you and your company. Appearance does count.



CASIO is a registered trademark of CASIO Computer Co., Ltd. in Japan. DLP, the DLP logo and the DLP medallion are trademarks of Texas Instruments. XGA is a registered trademark of International Business Machines Corporation in the United States. Windows and PowerPoint are registered trademarks of Microsoft Corporation in the USA and/or other countries. Other product names or company names on this specification sheet are either trademarks or registered trademarks of their respective owners. Specifications subject to change without notice.

Visit: [www.superslimprojector.com](http://www.superslimprojector.com)

## SPECIFICATIONS Model : XJ-S41

### Basic Specifications

Brightness(lumens)	Eco-Mode: OFF	2500 lumens
	Eco-Mode: ON	2000 lumens
Contrast Ratio	Telephoto mode	1800:1
Lamp	High-pressure mercury lamp	210W
Keystone Correction	Auto	+30°
	Manual	±30°
Focusing		Manual focus (electric)
Projection Lens	Zoom Ratio	Optical 2X electric zoom
Projection Screen Size		15 ~ 300-inch
Projection Range	60-inch screen	5.57 feet to 11.15 feet
	100-inch screen	9.18 feet to 18.37 feet
	Minimum	2.75 feet
	Projection ratio	1.4-2.8:1
Projection System		DLP® system
Display Element		0.55-inch DLP® chip
		786,432 pixels (1,024 x 768)
Color Reproduction		Full color (16.77 million colors)
Hor./Vert. Frequency		See attached sheet
Power Source		AC100~240V, 50/60Hz
Dimensions		10.62" x 7.83" x 1.69"
		Excluding projections (1.25" at thinnest point)
Weight		3.96 lbs.
Security Compatibility	Kensington Compatible	yes
	Power ON password	yes
Power Consumption	Operating	270W (Eco-Mode:220W)
Ceiling Mounting Possible		Yes when used with the ceiling mount lamp

### Interface Specifications

RGB Input	Input terminal	RGB mini D-Sub 15 pin x 1 Also use as YcbCr/YPbPr input
	True resolution	XGA (1,024 x 768)
	Compressed	Maximum SXGA+ (1,400 x 1,050)
Audio	Input	3.5mm mini-jack
	Output	1 W speaker
		3.5mm mini-jack ( sharing input terminal )
Video	Signal input	NTSC/PAL/PAL-N/PAL-M/PAL60/SECAM
	Input terminals	Composite: 3.5mm mini-jack ( sharing audio terminal ), YCbCr/YPbPr

### Others

Usage Environment	Operating temperature	5~35°
	Operating humidity	20~80% (non-condensation)
Lamp Life (hour)		2,000h
Remote Range *1:Front: within 30 degrees up, down, left, right Back: within 30 degrees left and right, within 5 to 30 degrees up, down		16.40 feet maximum *1
		Wireless remote controller (YT-35)
		AC cord
		RGB cable
		AV cable
		CD-ROM
		Soft case