

SVGA Ultraportable DLP™ Projector



EIP-200

2000 ANSI Lumens!

We're taking LCD & DLP™ projection to a whole new level!

Get the film-like imaging of DLP™ technology in a projector with conference room brightness



EIKI

PROJECTORS

EIKI MEANS PROJECTORS ... AND MORE!

KEY FEATURES:

- ▼ 2000 ANSI Lumens bright, 85% uniformity, and 2000:1 Contrast Ratio.
- ▼ DLP™ imaging technology delivers a "seamless" high contrast image.
- ▼ True SVGA resolution. SXGA+, SXGA, XGA, SVGA, VGA & MAC compatible.
- ▼ Smart data compression/expansion, and video scaling.
- ▼ Convenient Manual Zoom and Focus Lens.
- ▼ Preset image offset. Vertical digital keystone correction.
- ▼ Accepts Composite, S, and Component Video in all major standards.
- ▼ Displays both Regular 4:3 and Widescreen 16:9 ratio video formats.
- ▼ Supports most HDTV resolutions.
- ▼ Sealed Optics: no air filter to maintain.
- ▼ Extremely quiet: operating noise only 30 dBA in Eco mode.
- ▼ System Lock function. Keylock function.
- ▼ Menu Driven Help System. Power Management function.
- ▼ Wireless remote control.
- ▼ 3 Year* Projector Warranty!

EIP-200



Hg

Lamp Contains Mercury.
Do not put in trash. Dispose-of-as
Hazardous Waste, according to
Local, State or Federal Laws.



INCLUDED ACCESSORIES:

Owner's Manual. Quick Guide. AC Power Cord. Lens Cover. VGA-type Computer Input Cable (HD15~HD15). Wireless Remote Control & batteries (AAx2). Component Video Input Cable (HD15~3-RCA). RS-232 Control Adapter (DB9~9 Pin DIN).

OPTIONAL ACCESSORIES:

Replacement Lamp. Ceiling Mount. Ceiling Post and Plate. ATA-Style shipping Case with Wheels and Telescoping Handle. EZ-250 Local Control. NPC-1 Network Control.

EIKI

PROJECTORS

Eiki International, Inc.

Touchboards

205 Westwood Ave, Long Branch, NJ 07740
Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com

Specifications subject to change without notice.

©2005 EIKI International, Inc. Printed in the USA. 09/12/05

SPECIFICATIONS: EIP-200

Screen Brightness Standard 2,000 / Eco 1,740 ANSI Lumens
Illumination Uniformity 85%
Size of Color Palette 16.7 Million
Contrast Ratio 2000:1 (Full ON/OFF)
Horizontal Resolution 520 TV Lines (DTV 720p)
Projection Lamp 275 Watt VIP
Estimated Lamp Life Standard: 2000 / Eco: 3000 Hours of Use
Imaging System 0.55 in. DDR SVGA DMD™
Color System 4-segment, 3X speed color wheel
Screen Pixels (800 x 600) in stripe configuration
Total Pixels 480,000
Lens Type Manual Zoom and Focus
Lens Specs Speed: f:2.4~2.6; FL: 0.75~0.86 in. (19~21.9 mm)
Lens Ratios Zoom Range: 1.15:1; Throw:Width: 1.72~1.99:1
Image Diagonal 40~300 in. (102~762 cm)
Image Width 2.67~20 ft. (0.81~6.1 m)
Throw Distance 4.6~39.8 ft. (1.4~12.2 m)
Front Elevation / Maximum Tilt up to 8° up
Anti Keystone Fixed Image Offset, 110.5% of Image Height, up
Vertical Keystone Correction Digital: up-to 13° up or down.
Scanning Frequency Auto: H Sync. 15-70 kHz; V Sync. 43-85 Hz
Dot Clock 12 ~ 108 MHz
Image Orientation Normal, Reversed, Inverted
Local Control / Power Management Full Function / Auto Shut-Off
Remote Projector Control Wireless (Infra Red) x 1
RS-232 Control Port Mini DIN 9 Pin x 1
Computer Native Resolution 800 x 600 (SVGA)
Computer: Compatibility SXGA+, SXGA, XGA, SVGA, VGA & MAC 13~21
Computer: Formats 1400x1050 through 640x480
Computer: Image Sizing Normal or Smart Compressed or Expanded
Video Color Systems NTSC / PAL / SECAM / NTSC 4.43 / PAL-M&N
Video: Aspect Ratios Supported Normal 4:3 and Wide Screen 16:9
Video: Image Resizing Video Scaling Technology
Video Resolutions Supported:

SDTV 480i/p, 540p, 576i
EDTV 480p, 576p
HDTV 720p (50/60), 1035i (50/60), 1080i (50/60)

Signal Inputs:

1. Computer / Component (with breakout cable) HD15 x 1
2. Computer / Component (with breakout cable) HD15 x 1
plus: Audio shared between Inputs 1 & 2 Stereo: Mini Stereo x 1
3. S-Video S-Video x 1
4. Composite RCA x 1
plus: Audio shared between Inputs 3 & 4 Stereo: RCA x 2 (L&R)

Signal Outputs:

- Computer / Component shared between Input 1 & 2 HD15 x 1
plus: Audio shared between Inputs 1 ~ 4 Stereo: Mini Stereo x 1 (variable)

Audio: Amplifier Mono: 2 Watt
Audio: Built In Speaker 1.6 x 1.1 in. (4 x 2.85 cm) oval x 1
Fan Noise 33 dBA Standard, 30 dBA in Eco mode
Cabinet Size (HxWxD) 4.3 x 12.4 x 11.0 in. (109 x 315 x 280 mm.)
Overall Size (HxWxD) 4.7 x 12.4 x 11.6 in. (120 x 315 x 295 mm.)
Weight 8.6 lb. (3.9 kg)
Packaged Size (HxWxD) 10.7 x 17.4 x 18.1 in. (272 x 441 x 459 mm.)
Packaged Weight 16.3 lb. (7.4 kg)
Power Requirements 100-240V AC, 50/60Hz
Power Consumption / Heat 350 W / 922 BTU/hr (233 Kcal/hr)
Power Consumption / Heat - Eco 196 W / 669 BTU/hr (169 Kcal/hr)
Power Cord 6' (1.8 M) Type 3, Detachable
Safety Compliance UL / cUL
Security Facilities Kensington® Security Slot
Operating Temperature 41~95°F (5~35°C)
User Maintenance Clean Air Intake, Replace Lamp
Warranty: Projector 3 Yr. / 6000 Hr. *(Parts & Labor to Correct Defects)
Warranty: Lamp 90 Days (Failed Lamp Replaced Pro-Rata
* Whichever occurs first

Talk to your EIKI Dealer... the "pro" in projectors.

