




EIP-10V

A-key to better communications.

KEY FEATURES: Model EIP-10V

- Self-Contained Multi-Source Projection System: just add your computer.
- Includes XGA Projector, DVD Player, Media Card Player, TV Tuner.
- Weights about 10.5 lbs! Combines all these devices in one compact package.
- DLP™ projector delivers 1800 ANSI Lumens and a 2200:1 contrast ratio.
- True XGA resolution. SXGA, XGA, SVGA and VGA compatible.
- Quiet operation: operating noise about 32 dBA (typical).
- Smart data compression / expansion, and video scaling.
- Precision optical engine and manual zoom and focus lens.
- Preset image offset. Vertical digital keystone correction. 32x digital zoom.
- Accepts Composite, S, and Component Video (i/p) in all major standards.
- Displays normal 4:3 and Widescreen 16:9 ratio video formats.
- Supports HDTV at 1080i, 1035i & 720p. Supports SD at 480i/p & 575i/p.
- Built-in DVD player with "Intelligent Progressive Scan" for film-like image.
- Media Card Player supports most Movie, Photo and Audio media.
- 5.1 Channel Audio Output. Wireless Audio Output (speakers optional).
- Wireless remote controls all included devices. Carry case included.
- 3 Year* System Warranty!



EIP-10V

Included Accessories: Quick Start Guide. Owner's Manual. North America 3-prong grounded and polarized AC Power Cord & 2-prong polarized Adapter with ground wire. European 2-prong AC Power Cord. Lens Cover & Retainer. VGA type Computer Input Cable (HD15 ~ HD15). Mac Adapter. Computer Audio In/Out Cable (Stereo Mini~Stereo Mini). Audio Mono ~ Stereo "Y" Cable (RCA x 1 ~ RCA x 2) Wireless Remote C with 2 AAA batteries. Padded Carry Bag with Shoulder Strap.

Optional Accessories: Replacement Lamp. Wireless Speakers. Ceiling Mount. Ceiling Post and Plate.

SPECIFICATIONS: Model EIP-10V

DATA/VIDEO PROJECTOR

Screen Brightness	1800 ANSI Lumens
Illumination Uniformity	80%
Size of Color Palette	16.7 Million
Contrast Ratio	2200:1 (Full ON/OFF)
Horizontal Resolution	480 TV Lines (S-Video)
Projection Lamp	250 Watt P-VIP
Estimated Lamp Life	2000 Hours Normal, 3500 Hours Eco
Imaging System	0.7" DDR XGA DMD 4 Segment Color Wheel RGWB
Screen Pixels	1024x768 in stripe configuration
Total Pixels	786,432 (1024x768)
Lens Type	Manual Zoom and Focus
Lens Specs	Speed: f:2.8~3.1; FL: .1.02~1.18 in. (25.8~30.0 mm)
Lens Ratios	Zoom Max:Min: 1.2:1; Throw:Width: 1.8~2.1:1
Image Diagonal	40~300 in. (101.6~762 cm)
Image Width	2.5~20 ft. (0.76~6.1 m.)
Throw Distance	4.8~36.1 ft. (1.46~11 m.)
Front Elevation / Maximum Tilt	up to 15° up / +/- 45°
Anti Keystone	Fixed Image Offset, Ratio (Top:Bottom) est. 10:0 (100%)
Vertical Keystone Correction	Digital: up to 12° up or down
Scanning Frequency	Auto: H Sync. 15-82 kHz; V Sync. 50-85 Hz
Dot Clock	157.5 MHz
Image Orientation	Normal, Reversed, Inverted
Remote Control	Wireless (Infra Red) x 1
Computer Native Resolution	1024x768 (XGA)
Computer: Compatibility	SXGA, XGA, SVGA, VGA
Computer: Formats	1280x1024, 1024x768, 800x600, 640x480
Computer: Higher Resolutions	Displayed Smart Compressed
Computer: Lower Resolution	Displayed Smart Expanded
Computer Input: Data	Analog - HD15 x 1
Audio	Stereo - MiniStereo x1
Computer Output	(Monitor) HD15 x 1
Video Color Systems	NTSC / PAL / SECAM / NTSC 4.43 / PAL-M & N
Video: Resolutions	480i/p, 576i/p, 720p, 1035i, 1080i
Video: Formats Supported	Normal 4:3 and Wide Screen 16:9
Video: Image Sizing	Video Scaling Technology
Video Input: 1. Composite	RCA x 1 (Y)
2. S-Video	S-Video x 1 (Y/C)
3. Component	RCA x 3 (Y, Pb/Cb, Pr/Cr)
Audio	Stereo: RCA x 2 (L&R)

INCLUDED SOURCE DEVICES

- DVD Player:** Slot-in type. Progressive Scan with 2-3 Pulldown Support. Supports DVD, VCD, CD, Interactive VCD, S-VCD, MP3, JPG file
- Media Card Player:** 3 Bays: CF / SM / MD / MS / SD / MMC media Plays Photo (JPG) Movie (MPEG1 & 2) and Music (MP3) files
- TV Tuner:** "F" Terminal x 1 NTSC Channels 1 ~ 125

OVERALL SYSTEMS

- Internal Audio: Amplifier Mono: 2 Watts
- Speaker 1.5 in. (4.0 cm) x 1
- Audio Output (Wired) Stereo - MiniStereo x 1
- 5.1 Channel - MiniStereo x 3
- Operating Noise 32dBA typical
- Cabinet Size** (HxWxD) 3.6 x 14.7 x 11.4 in. (9.1 x 37.4 x 29.0 cm.)
- Weight 10.4 lbs. (4.71kg)
- Packaged Size (H x W x D) 12.0 x 19.5 x 16.0 in. (30.5x 49.5 x 40.6 cm.)
- Packaged Weight 26.5 lb (12kg)
- Power Requirements 100-240V AC, 50/60Hz
- Power Consumption / Heat Normal 330 W /1126 BTU/hr (284 Kcal/hr)
- Power Cord 6' (2M) Type 3, Detachable
- Safety Compliance FCC Class B, cUL Listed
- Security Facilities Kensington® Security Slot
- Operating Temperature 41~95°F (3~35°C)
- User Maintenance Replace Lamp
- Warranty: Projector 3 Yr. / 6000 Hr. *(Parts & Labor to Correct Defects)
- Warranty: Lamp 90 Days (Failed Lamp Replaced Pro-Rata
- * Whichever occurs first

OPTIONAL WIRELESS STEREO SOUND SYSTEM

- Built-in Wireless Audio Transmitter** Frequency: 2400 MHz band
- Channels: 8; Spacing: 7MHz (min)
- Optional Wireless Amplified Speakers 25W x 2
- Size (each) 10.6 x 6.7 x 7.1 in. (27 x 17 x 18 cm)
- Weight - pair 18.3 lb (8.3 kg)
- Packaged Size (pair) 14 x 19 x 10 in. (35.5 x 48.3 x 25.4 cm)
- Packaged Weight (pair) 21.2lb (9.6 kg)
- Power Requirements: 100-240V AC, 50/60Hz
- Power Consumption: 100W

The Lamp in this projector contains trace elements of mercury. As a public service EIKI publishes the following notice.

Lamp contains Mercury. Do not put in trash. Dispose of as Hazardous Waste, according to Local, State or Federal Laws.

Specifications subject to change without notice. ©2004 Eiki International, Inc. Issued May 24, 2004.



205 Westwood Ave, Long Branch, NJ 07740
 Phone: 866-94 BOARDS (26273) / (732)-222-1511
 Fax: (732)-222-7088 | E-mail: sales@touchboards.com