

XGA Ultraportable DLP™ Projector

EIP-2500 2500 ANSI Lumens!

We're taking LCD & DLP™ projection to a whole new level!

KEY FEATURES:

- ▼ 2500 ANSI Lumens, 85% uniformity, up to 2000:1 Contrast Ratio.
- ▼ DLP™ imaging technology delivers a "seamless" high contrast image.
- ▼ True XGA resolution. SXGA+, SXGA, XGA, SVGA, and VGA compatible.
- ▼ Smart data compression / expansion, and video scaling.
- ▼ Convenient manual zoom and focus lens.
- ▼ Preset image offset. Vertical digital keystone correction.
- ▼ Accepts Composite, S, and Component Video in all major standards.
- ▼ Displays both 4:3 and Widescreen 16:9 ratio video formats.
- ▼ Supports all HDTV resolutions.
- ▼ System Lock function. Keylock function.
- ▼ Menu Driven Help System. Power Management function.
- ▼ Wireless remote control.
- ▼ 3 Year* Projector Warranty!



SPECIFICATIONS: EIP-2500

| | |
|----------------------------------|---|
| Screen Brightness | 2500 ANSI Lumens |
| Illumination Uniformity | 85% |
| Size of Color Palette | 16.7 Million |
| Contrast Ratio | 1600:1 (Full ON/OFF) (up to 2000:1 in bright boost) |
| Horizontal Resolution | 600 TV Lines (DTV 720p) |
| Projection Lamp | 275 Watt VIP |
| Estimated Lamp Life | up to 3000 Hours |
| Imaging System | 0.544 in. DDR XGA DMD™ |
| Color System | 4-segment, 3X speed color wheel |
| Screen Pixels | 1024 x 768 in stripe configuration |
| Total Pixels | 786,432 |
| Lens Type | Manual Zoom and Focus |
| Lens Specs | Speed: f:2.4~2.6; FL: 0.75~0.86 in. (19~21.9 mm) |
| Lens Ratios | Zoom Range: 1.15:1; Throw:Width: 1.72~1.99:1 |
| Image Diagonal | 40~300 in. (102~762 cm) |
| Image Width | 2.67~20 ft. (0.81~6.1 m) |
| Throw Distance | 4.6~39.8 ft. (1.4~12.2 m.) |
| Front Elevation | up to 8° up |
| Anti Keystone | Fixed Image Offset, 110.3% of Image Height, up |
| Vertical Keystone Correction | Digital: up to 13° up or down |
| Scanning Frequency | Auto: H Sync. 15-70 kHz; V Sync. 45~85 Hz |
| Dot Clock | 108 MHz |
| Image Orientation | Normal, Reversed, Inverted |
| Local Control / Power Management | Full Function / Auto Shut-Off |
| Remote Projector Control | Wireless (Infra Red) x 1 |
| RS-232 Control Port | Mini DIN 9 Pin x 1 |
| Computer Native Resolution | 1024 x 768 (XGA) |
| Computer: Compatibility | SXGA+, SXGA, XGA, SVGA, VGA & MAC |
| Computer: Formats | 1280x1024, 1024x768, 800x600, 640x480 |
| Computer: Higher Resolutions | Displayed panned or Smart Compressed |
| Computer: Lower Resolution | Displayed normal or Smart Expanded |

| | |
|---|--|
| Video Compatibility | NTSC / PAL / SECAM / NTSC 4.43 / PAL-M&N |
| Video HD Compatibility | 480i/p, 540p, 576i/p, 720p, 1035i, 1080i |
| Formats Supported | Normal 4:3 and Wide Screen 16:9 |
| Video: Image Sizing | Video Scaling Technology |
| Signal Inputs | |
| 1. Computer / Component (with breakout cable) | HD15 x 1 |
| 2. Computer / Component (with breakout cable | HD15 x 1 |
| plus Audio shared between Inputs 1 & 2 | Stereo: Mini Stereo x 1 |
| 3. S-Video | S-Video x 1 |
| 4. Composite | RCA x 1 |
| plus Audio shared between Inputs 3 & 4 | Stereo: RCA x 2 (L&R) |
| Signal Outputs | |
| Computer / Component shared between Input 1 & 2 | HD15 x 1 |
| plus: Audio shared between Inputs 1 & 2 | Stereo: Mini Stereo x 1 |
| Audio: Amplifier | Mono: 2 Watt |
| Audio: Built In Speaker | 1.6 x 1.1 in. (4 x 2.85 cm) oval x 1 |
| Fan Noise | 37 dBA Standard, 35 dBA in Eco mode |
| Cabinet Size (HxWxD) | 4.7 x 12.4 x 11.6 in. (120 x 315 x 295 mm.) |
| Weight | 8.6 lb. (3.9 kg) |
| Packaged Size (HxWxD) | TBA |
| Packaged Weight | TBA |
| Power Requirements | 100-240V AC, 50/60Hz |
| Power Consumption / Heat | 350 W / 922 BTU/hr (233 Kcal/hr) |
| Power Consumption / Heat - Eco | 196 W / 669 BTU/hr (169 Kcal/hr) |
| Power Cord | 6' (1.8 M) Type 3, Detachable |
| Safety Compliance | UL / cUL |
| Security Facilities | Kensington® Security Slot |
| Operating Temperature | 41~95°F (5~35°C) |
| User Maintenance | Clean Air Intake, Replace Lamp |
| Warranty: Projector | 3 Yr. / 6000 Hr. *(Parts & Labor to Correct Defects) |
| Warranty: Lamp | 90 Days (Failed Lamp Replaced Pro-Rata |
| | * Whichever occurs first |

INCLUDED ACCESSORIES:

Owner's Manual. Setup Guide CD. System Lock Caution. Quick Guide. AC Power Cord. Lens Cover. VGA-type Computer Input Cable (HD15 ~ HD15). Wireless Remote Control & Batteries (AA x 2). Component Video Input Cable (HD15~3-RCA) RS-232 Control Adapter (DB9~8-Pin DIN).

OPTIONAL ACCESSORIES:

Replacement Lamp. Ceiling Mount. Ceiling Post and Plate. EZtrol® Local Control. NPC-1 Network Control. NetControl® Advanced Software.



EIKI MEANS PROJECTORS ... AND MORE!

Lamps Contain Mercury. Do not put in trash. Dispose-of-as Hazardous Waste, according to Local, State or Federal Laws.

Eiki International, Inc.
Touchboards
 205 Westwood Ave, Long Branch, NJ 07740
 Phone: 866-94 BOARDS (26273) / (732)-222-1511
 Fax: (732)-222-7088 | E-mail: sales@touchboards.com

Specifications subject to change without notice.
©2005 EIKI International, Inc. Printed in the USA. 07/05/05