

EIKI Lens Specifications for the EIP-3500, EIP-3000N, EIP-2500 and EIP-200 June 7, 2006
Native 4:3 Aspect Ratio Projectors

EIP-3500

XGA DLP PROJECTOR

Resolution: XGA (1024x768)

Aspect Ratio: (3 High by 4 Wide by 5 Diagonal)

Aperture: 0.541 in. wide

EIKI P/N: Ref. T/W Shift (T:B)

Lens

Screen Dimensions.

H'	2	3	4	5	6	7.5	9	12	15
W'	2.66	4	5.33	6.67	8	10	12	16	20
D"	39.9	60	80	100	120	150	180	240	300

Standard	1.55	102.2% up (fixed)	0.839"~1.244" Power, Zoom (21.3~31.6 mm) f:2.0~2.5	0.84 1.24	4.1	6.2	8.3	10.3	12.4	15.5	18.6	24.8	31.00
	2.30												36.8 46.00

EIP-3000N

XGA DLP PROJECTOR

EIP-3000N Resolution: XGA (1024x768)

Aspect Ratio: (3 High by 4 Wide by 5 Diagonal)

Aperture: 0.439 in. wide

EIKI P/N: Ref. T/W Shift (T:B)

Lens

Screen Dimensions.

H'	2	3	4	5	6	7.5	9	12	15
W'	2.66	4	5.33	6.67	8	10	12	16	20
D"	40	60	80	100	120	150	180	240	300

Standard	1.72	110.6% up (fixed)	0.736"~0.847" Manual, Zoom (18.7~21.5 mm) f:2.4~2.6	0.75 0.86	4.5	6.8	9.1	11.4	13.6	17.0	20.4	27.3	34.1
	1.99												31.4 39.3

EIP-2500

XGA DLP PROJECTOR

EIP-2500 Resolution: XGA (1024x768)

Aspect Ratio: (3 High by 4 Wide by 5 Diagonal)

Aperture: 0.439 in. wide

EIKI P/N: Ref. T/W Shift (T:B)

Lens

Screen Dimensions.

H'	2	3	4	5	6	7.5	9	12	15
W'	2.66	4	5.33	6.67	8	10	12	16	20
D"	40	60	80	100	120	150	180	240	300

Standard	1.72	110.3% up (fixed)	0.748"~0.862" Manual, Zoom (19~21.9 mm) f:2.4~2.6	0.75 0.86	4.5	6.8	9.1	11.4	13.6	17.0	20.4	27.3	34.1
	1.99												31.4 39.3

EIP-200

SVGA DLP PROJECTOR

EIP-200 Resolution: SVGA (800x600)

Aspect Ratio: (3 High by 4 Wide by 5 Diagonal)

Aperture: 0.434 in. wide

EIKI P/N: Ref. T/W Shift (T:B)

Lens

Screen Dimensions.

H'	2	3	4	5	6	7.5	9	12	15
W'	2.66	4	5.33	6.67	8	10	12	16	20
D"	40	60	80	100	120	150	180	240	300

Standard	1.72	110.9% up (fixed)	0.748"~0.862" Manual, Zoom (19~21.9 mm) f:2.4~2.6	0.75 0.86	4.6	6.9	9.2	11.5	13.8	17.2	20.7	27.6	34.50
	1.99												31.8 39.70

Notes

Image Height for 16:9: width stays the same as 4:3 (ignore Diagonal)	H'	1.50	2.25	3.00	3.75	4.50	5.63	6.75	9.00	11.25
----------------------------------------------------------------------	----	------	------	------	------	------	------	------	------	-------

How to use the T/W column. If your screen size does not appear on this chart, use the T/W column to find the lens you need.

Divide the Throw distance by the screenWidth to get your "target T/W number". Then, look for a lens with a T/W range that covers it.

Understanding Lens Shift. The number in the Shift column expresses the projector's position relative to the image height.

50% positions the projector's lens perpendicular to the center of the image (on axis). 100% up positions the projector's lens perpendicular to the bottom edge of the image. 102.2%, 110.3% and 110.9% up positions the projector's lens perpendicular to a point 2.2%, 10.3% or 10.9% of the image height respectively, below the image.

These charts are a simulation. Effective Focal Length (EFL) most accurately represents lens behavior, and drives the calculations..

Calculations are from the front glass of the lens and accurate to approximately +/- 3%. Specifications are subject to change without notice.