



Projectors... and more!

KEY FEATURES: Model EIP-WX5000

5200 ANSI Lumens bright, at 90% uniformity, and a 1800:1 contrast ratio.
 WXGA (16:10) resolution. UXGA ~ VGA, MAC and Workstation compatible.
 3 DLP™ imaging technology delivers a "seamless" high contrast image.
 Power Zoom and Focus Lens. Optional Wideangle and Telephoto lenses.
 Horizontal & Vertical Lens Shift. H, V & Geometric Keystone Correction.
 Dual Lamp System provides redundancy and permits 4 brightness levels.
 Wireless/wired remote. Wireless remote mouse. Mechanical shutter.
 RS-232 System and Network Control Compatible: Built in D-sub 9 and RJ45.
 Smart data compression / expansion, and video scaling. sRGB Compatibility.
 Displays both Regular 4:3 and Widescreen 16:9 ratio video formats.
 Converts Interface video to Progressive scan. 2-3 Pulldown Support.
 Accepts Analog and Digital Video input signals up to 1080p.
 Power Management, Keylock Security, and Custom Warmup Screen options.
 Unique Projector Stack Control and VideoWall Signal Division features.
 3 Year* Projector Warranty!

Included Accessories: Printed Quick Setup Guide and Owner's Manual. Quick Setup Guide, Owner's Manual and CAD Drawings on CD ROM. 6.0 ft (1.8 M) AC Power Cord. Lens Cover. VGA-type Computer Input Cable (D-sub 15). Wireless/wired Remote with Mouse Control & 2 x AA batteries. Remote Mouse Receiver on 5.25 ft (1.6M) USB-A cable.

Optional Accessories: Replacement Lamps. Wideangle and Telephoto Lenses. ATA-Style Shipping Case with Wheels and Telescoping Handle. Ceiling Mount. Ceiling Post and Plate.

SPECIFICATIONS: Model EIP-WX5000

Screen Brightness up to 5200 ANSI Lumens
 Illumination Uniformity 90%
 Size of Color Palette 8-Bit/16.7 Million
 Contrast Ratio 1800:1
 Horizontal Resolution 550 TV Lines (HDTV)
 Projection Lamp 280 Watt UHP x 2
 Estimated Lamp Life up to 3000 Hours of Use
 Imaging System 0.65" DDR 3 DLP® DMD®
 Screen Pixels 1,024,000 (1280x800) in stripe configuration
 Lens Type Power Zoom and Focus
 Lens Specs Speed: f:2.5; FL: 1.00~1.26in. (25.5~32.0 mm)
 Lens Ratios Zoom Max:Min: 1.25:1; Throw:Width: 1.8~2.5:1
 Image Diagonal 60~280 in. (152.4~711.2 cm)
 Image Width 4.2~19.8 ft. (1.3~6.03 m.)
 Throw Distance 7.9~45 ft. (2.4~13.7 m.)
 Front Elevation / Maximum Pitch up to 5° up / 9° off the horizontal
 Vertical Anti Keystone Power Lens Shift (Top:Bottom) ±66%
 Horizontal Anti Keystone Power Lens Shift (L:R~R:L) ±35%
 Vertical Keystone Correction Digital: 40° up or down
 Horizontal Keystone Correction Digital: 30° left or right
 Geometric Keystone Correction Digital
 Scanning Frequency Auto: H Sync. 15-126 kHz; V Sync. 43-200 Hz
 Dot Clock 12~230 MHz
 Image Orientation Normal, Reversed, Inverted
 Local Control / Power Management Full Function / Auto Shut-Off
 Remote Projector Control (with Mouse) Wireless/wired x 1
 Wired Remote Port MiniStereo x 1
 RS-232 Port Dsub 9-pin x 1
 LAN Port RJ45 x 1
 Computer Native Resolution 1280x800 (WXGA)
 Computer: Compatibility ...UXGA, SXGA+, SXGA, WXGA, XGA, SVGA, VGA
 MAC & Workstation
 Computer: Formats 1600 x 1200 through 640 x 480
 Computer: Image Sizing Normal, or Smart Compressed or Expanded
 Video: Color Systems NTSC/PAL/SECAM/NTSC 4.43 / PAL-M&N
 Video: Aspect Ratios Supported 4:3 & 16:9
 Video: Image Sizing Video Scaling Technology

Video: Resolutions Supported

SDTV (Composite, S-Video, Component) 480i / 540p, 576i
 EDTV (DVI w/HDCCP) 480p, 576p
 HDTV (DVI w/HDCCP) 720p (60), 1035i (60), 1080i/p (50/60)

Signal Inputs:

HDMI HDMI x 1
 DVI-D(w/HDCCP) DVI-D x 1
 plus Audio: Stereo: MiniStereo x 1
 Computer/Component 1: D-sub 15 x 1
 plus Audio: Stereo: MiniStereo x 1
 Computer/Component 2: BNC x 5
 plus, Audio: Stereo: MiniStereo x 1
 S-Video S-Video x 1
 plus, Audio: Stereo: MiniStereo x 1
 Composite RCA x 1
 plus, Audio: Stereo: MiniStereo x 1

Outputs

Computer/Component D-sub 15 x 1
 Audio: Line Stereo: MiniStereo x 1
 Audio: Amplifier Stereo: 3 Watts
 Audio: Built In Speakers ...Stereo: 1.3x2.6in. (3.38x6.8 cm) (oval) x 2

Operating Noise as low as 34 dBA
 Cabinet Size (HxWxD) 7.5 x 19.7 x 25.1 in. (190 x 500 x 637 mm.)
 Weight 58.4 lbs. (26.5 kg)
 Packaged Size 15.8 x 28.4 x 34.3 in. (400 x 720 x 870 mm.)
 Packaged Weight 77.2 lb (35 kg)
 Power Requirements 100-240V AC, 50/60Hz
 Power Consumption up to 755 W
 Heat up to 2578 BTU/hr. (649Kcal/hr)
 Power Cord 6' (1.8M) Type 3, Detachable
 Electrical Safety Compliance UL / cUL IEC
 Electromagnetic Compatibility FCC Part 15 Class A, CE Mark
 Security Facilities Kensington® Security Slot
 Operating Temperature 41~104°F (5~40°C)
 User Maintenance Clean Air Filter, Replace Lamp
 Warranty (to original end use customer)

Projector : 3 Yr. / 6000 Hr. *(Parts & Labor to Correct Defects)
 Lamp: 90 Days (Failed Lamp Replaced Pro-Rata)
 * Whichever occurs first

Lamp contains Mercury. Do not put in trash. Dispose of as Hazardous Waste, according to Local, State or Federal Laws.


Specifications subject to change without notice. ©2008 Eiki International, Inc. Issued June 15, 2008.

Eiki International, Inc., 30251 Esperanza, Rancho Santa Margarita, CA 92688-2132. Tel: 800-242-3454; Fax: 800-457-3454, E-mail: usa@eiki.com

In Canada: 310 First St., Unit 2, P.O. Box 156, Midland, ON L4R 4K8. Tel: 800-563-3454, Fax: 800-567-4069, E-mail: canada@eiki.com

Visit our World Wide Web site: <http://www.eiki.com>

WXGA Widescreen 3 DLP® Projector



EIP-WX5000