

LC-SXG400

SXGA "G" Series Projector
4200 ANSI Lumens

Get the rich color imaging of 3 panel LCD technology in an installation projector with unparalleled brightness and compatibility.

- ▼ 4200 ANSI Lumens bright, at 90%+ uniformity, and a 1300:1 contrast ratio.
- ▼ 3 panel LCD imaging for rich, color saturated computer and video projection.
- ▼ SXGA+ resolution. Smart data compression/expansion, and video scaling.
- ▼ Includes most professional input configurations, including 5BNC and DVI.
- ▼ Accepts analog and digital computer input, analog and digital w/HDCP video.
- ▼ Compatible with computer sources up to UXGA, Video sources up to 1080i
- ▼ Power zoom and focus. V & H power lens shift. Digital keystone correction.
- ▼ Optional Wideangle and Telephoto lenses. Instant Lens Change System
- ▼ Converts Interlace to Progressive scan. 3-2 (and 2-2) pulldown support.
- ▼ Variable Power Management Option. Optional Local or Remote Keylock
- ▼ Custom Warm-up Screen Image Option. Built-in Color Auto Picture Control
- ▼ Wireless/wired remote w/mouse & laser pointer. 50%~+700% digital zoom.
- ▼ 3 Year* Projector Warranty!



Outstanding Features


1. Power Lens Shift: Up 50%, Left or Right 15%.
2. High brightness and contrast. Optional lenses 0.8~11.3:1 (T:W).
3. Physically centered lens. Projector supports pitch through 360°.
4. Push-button lens replacement (no dismantling required).
5. One-way cooling system (1 in & 1 out port) simplifies installation.
6. Front-accessed high-capacity air filter simplifies maintenance.
7. Clogged air filter detection with both LED and on-screen warning.
8. Rear-accessed lamphouse makes lamp change easy
9. Built-in test pattern array for easy adjustments.

EIKI
Projectors... and more!

LC-SXG400 4200 ANSI Lumens

SPECIFICATIONS:

Brightness	up to 4200 ANSI Lumens
Illumination Uniformity	up to 90% (on axis)
Size of Color Palette	10 bit/1.07 Billion Colors
Contrast Ratio	up to 1300:1 (Full ON/OFF)
Projection Lamp	330 Watts NSHA x 1
Estimated Lamp Life	up to 3000 Hours of Use
Imaging System	1.0" Polysilicon active matrix TFT Panels x 3
Screen Pixels	1400 x 1050 in stripe configuration
Total Pixels	1,470,000 ((1400 x 1050) x 3)
Lens Type	Power Zoom & Focus
Lens Specs	Speed: f: 1.7~2.1; FL: 1.3~1.69 in. (33~43 mm)
Lens Ratios	Zoom Max:Min: 1.3:1; Throw: Width: 1.69~2.20:1
Image Diagonal	30~300 in. (76.2~762 cm)
Image Width	2.0~20 ft. (0.61~6.1 m)
Throw Distance (wide-tele)	3.9~32.8 ft. (1.2~10.0 m)
Front Elevation	up to 5° up
Maximum Pitch	anywhere up to 360° off the horizontal axis
Vertical Anti Keystone	Power Lens Shift, Up Only, 50%
Horizontal Anti Keystone	Power Lens Shift, Left or Right, 15%
Vertical Keystone Correction	Digital: up to 40° up or down
Scanning Frequency	Auto: H Sync. 15-100 kHz; V Sync. 50-100 Hz
Dot Clock	165 MHz Analog/130 MHz Digital
Image Orientation	Normal, Reversed, Inverted
Local Control/Power Management	Full Function/Auto Shut-off
Remote Projector & Mouse Control	Wireless/Wired x 1 w/Laser Pointer
Auxiliary Ports:	Mouse: USB-B x 1, Wired RC: MiniStereo x 1
Computer: Native Resolution	1400 x 1050 (SXGA+)
Computer: Compatibility	UXGA (analog only) & SXGA+ SXGA, WXGA, XGA, SVGA, VGA and MAC (analog & digital)
Computer: Formats	1600 x 1200 thru 640 x 480
Computer: Imaging Sizing	Normal, or Smart Compressed or Expanded
Video: System Compatibility	NTSC/PAL/SECAM/NTSC 4.43/PAL-M/N
Video: Compatibility	480i/p, 575i/p, 720p, 1035i, 1080i-50/60
Video: Formats Supported	4:3 and 16:9
Video: Image Resizing	Video Scaling Technology
Video: Systems	Composite, S-Video, Component Analog, & Digital
Inputs:	
1a. either: Analog Computer:	HD15 x 1
1b. or Digital Computer, or Digital Video w/HDCP	DVI-D x 1
plus Stereo Audio:	MiniStereo x 1
2a. either Analog Computer (RGBHV):	BNC x 5
2b. or Analog Video: (Y,Pb/Cb,Pr/Cr) (BNC x 3):	
plus, Stereo Audio:	MiniStereo x 1
3. either Composite Video:	RCA x 1
or S-Video:	S-Video x 1
plus, Stereo Audio:	RCA x 2
Outputs:	
Analog Computer:	HD15 x 1
Stereo Audio - Variable Line	Stereo: MiniStereo x 1
Audio: Amplifier	Mono: 1 Watt RMS Internal
Audio: Built in Speakers	1.1 in. (28 mm) x 1
Fan Noise	as low as 35 dBA
Overall Size (HxWxD)	6.46 x 13.7 x 17.48 in. (164 x 348.1 x 444 mm) (Including foot)
Weight	19.62 lbs. (8.9 kg)
Packaged Size (HxWxD)	14.6 x 19.3 x 23.3 in. (370 x 490 x 590 mm)
Packaged Weight	28.9 lbs. (13.1 kg)
Power Requirements	100-240V AC, 50/60 Hz
Power Consumption	up to 500 Watts
Heat	up to 1706 BTU (430 KC)
AC Power Cord	10' (3M) Type 3 detachable x 1
Safety Compliance	IEC (EN)60950, UL60950/CUL
Electromagnetic Compatibility	FCC Class B, CE Mark
Security Facilities	Kensington® Security Slot
Operating Temperature	41~95°F (5~35°C)
User Maintenance	Clean Air Filter, Replace Lamp
Warranty: (to the original end-use customer)	
Projector:	3 Years/6000 Hour Use* (Parts/Labor to Correct Defects)
Lamp:	90 days/500 Hours Use* (Failed Lamp Replaced Pro-Rata) *whichever occurs first



INCLUDED ACCESSORIES:

Quick Start Guide. Owner's Manual on CD-ROM.
AC Power Cord 10' (3M) Type 3, Detachable. Lens Cover.
VGA-type (Dsub15~Dsub15) Computer Input Cable.
Wireless/Wired Remote with Mouse Control and Laser
Pointer & 2 x AAA batteries, USB Cable for Computer
Mouse control. Serial (DB9~8DIN) control cable (RS-232).

OPTIONAL ACCESSORIES:

Replacement Lamp. Soft Carry Bag with Wheels and
Telescoping Handle. ATA-Style Shipping Case with Wheels
and Telescoping Handle. A Range of Wideangle and
Telephoto Lenses. Ceiling Mount. Ceiling Post and Plate.
PiNET Network Interface.

Talk to your EIKI Dealer... the "pro" in projectors.



205 Westwood Ave, Long Branch, NJ 07740
Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com

Eiki International, Inc.

30251 Esperanza, Rancho Santa Margarita, CA 92688-2130
Tel: 800-242-3454; Fax: 800-457-3454, E-mail: usa@eiki.com

In Canada, 310 First St.-Unit 2, P.O. Box 156, Midland, ON L4R 4K8
Phone: 800-563-3454, Fax: 800-567-4069 E-mail: canada@eiki.com

<http://www.eiki.com>

EIKI
Projectors... and more!

Specifications subject to change without notice.
©2008 EIKI International, Inc. Printed in the USA. 04/01/08