

Full Screen - 16:10

Resolution: WXGA (1280x800)

Aspect Ratio: (10 High by 16 Wide by 18.868 Diagonal)

Aperture: 0.5003 in. wide

Screen Dimensions.

H'	1.8	3.5	4.4	6.6	8.8	13.2
W'	2.8	5.7	7.1	10.6	14.15	21.2
D"	40	80	100	150	200	300

EIKI Part No.	Ref.	T/W	Shift/Limits	Standard Lens	EFL	Throw (Distance to Screen) in feet.					
LC-WB100											
Standard Lens		1.19	49:1	0.609" ~ 0.965" Manual, Zoom	0.60	3.4	6.7	8.4	12.6	16.8	25.2
		1.91	(fixed)	(15.5 ~ 24.5 mm) f:1.65 ~ 2.33	0.96	5.4	10.8	13.5	20.3	-	-

Example 1: Video Mode, 16:9 Source, Normal (default setting)

No scaling.

Projected Image: 1280x720 - full width - 40 black pixels top and bottom

H'	1.6	3.2	4.0	6.0	8.0	11.9
W'	2.8	5.7	7.1	10.6	14.2	21.2
D"	38.8	77.8	97.2	146.2	194.8	291.9

Example 2: Video Input, 4:3 Source, Normal (default) Setting

Signal is scaled proportionately to fit: maintains aspect ratio.

Projected Image: 1067x800 - full height, 107 black pixels left & right

H'	1.8	3.5	4.4	6.6	8.8	13.2
W'	2.4	4.7	5.9	8.8	11.7	17.6
D"	36.0	70.0	88	132	176	264

Example 3: Computer Mode, XGA (4:3) Source, True (optional) Setting

No scaling. (For Computer Input, XGA Source, Normal (default) Setting: see Example 2 (4:3).)

Projected Image: 1024x768 - 128 black pixels left & right, 16 black pixels top & bottom

H'	1.7	3.4	4.2	6.3	8.4	12.7
W'	2.3	4.5	5.6	8.4	11.3	16.9
D"	34.6	67.2	84	127	169	253

How to use the T/W column. If your screen size does not appear on this chart, use the T/W column to find the lens you need.Divide the Throw distance by the screen **Width** to get your "target T/W number". Then, look for a lens with a T/W range that covers it.**Understanding Shift/Limits.** The numbers in the Shift/Limits column express the projector positions possible as a ratio of the image heights

Above:Below a line drawn perpendicular to the screen between the lens and the screen. 1:1 = center of the image. The two sides of a ratio are cumulative, so the expression 7:-1 means that the bottom of the image starts 1/6'th of the image height above the imaginary line.

These charts are a simulation. Effective Focal Length (EFL) most accurately represents lens behavior, and drives the calculations..

Calculations are from the front glass of the lens and accurate to approximately +/- 3.5%. Specifications are subject to change without notice.

**205 Westwood Ave, Long Branch, NJ 07740****Phone: 866-94 BOARDS (26273) / (732)-222-1511****Fax: (732)-222-7088 | E-mail: sales@touchboards.com**