




LC-X50

XGA Boardroom Projectors

KEY FEATURES: Model LC-X50

3700 ANSI Lumens bright, at 90%+ uniformity, and a 1000:1 contrast ratio.
Extremely quiet operation: fan noise as low as 35 dBA in Eco-Mode.
Network connectivity with the optional Pj-to NetDirector Interface.
3 panel LCD imaging for rich, color saturated visuals.
Weighs only 19.6 lb. Compact and easy to store.
True XGA resolution. SXGA, XGA, SVGA, VGA and MAC compatible.
2 "VGA" (HD15) Computer Inputs & 2 Composite/Component Video Inputs.
A 3W Built-in Stereo Audio System, plus 5W External Speaker Output.
Smart data compression / expansion, and video scaling.
Power zoom and focus. Power lens shift. Digital keystone correction.
Wireless/wired remote with mouse and laser pointer. 7power digital zoom.
Accepts DVD & HDTV Component Video, plus Composite, and S-Video Input.
Displays both Regular 4:3 and Widescreen 16:9 ratio video formats.
Improved progressive scan with HDTV at 1080i and 2-3 pulldown support.
3 Year* Projector Warranty!



LC-X50

INCLUDED ACCESSORIES: Owner's manual. AC Power Cord. Lens Cover. VGA-type Computer Input Cable. Wireless/Wired Remote with Mouse Control and Laser Pointer. 2xAA batteries and 1.5M Wired Remote Cable. Serial control cable. USB Mouse Cable. Dust Cover.

OPTIONAL ACCESSORIES: Replacement Lamp. Soft Carry Bag. Luggage Style Carry Case with Wheels and Telescoping Handle. ATA-Style Shipping Case with Wheels and Telescoping Handle. Wideangle and Telephoto Lenses. Ceiling Mount, Ceiling Post and Plate. 33' (10M) Mouse Extension Cable. Pj-to-NetDirector Interface. EZtrol Local Control. NPC-1 Network Control.

SPECIFICATIONS: Model LC-X50

Screen Brightness	3700 ANSI Lumens / 2950 in Eco-Mode	Video: HDTV Compatability	480i/p, 575i/p, 720p, 1035i, 1080i, -50/60
Illumination Uniformity	90%	Video: Formats Supported	4:3, 16:9
Size of Color Palette	16.7 Million	Video: Systems	Composite, S-Video, Component (Y,Pb/Cb, Pr/Cr)
Contrast Ratio	1000:1 (Full ON/OFF)	Video: Image Resizing	Video Scaling Technology
Horizontal Resolution	800 TV Lines	Inputs:	
Projection Lamp	300W NSH / operated at 240W in Eco-Mode	1. Computer :	HD15 x 1, AudioStereo: MiniStereo x 1 (L&R)
Estimated Lamp Life	2000 Hours	2. Computer :	HD15 x 1, Audio Stereo MiniStereo x 1 (L&R)
Imaging System	1.3" PolySilicon active matrix TFT Panels x 3	3. Video: RCA x 3 (Composite/Component: Y,Pb/Cb,Pr/Cr)	
Screen Pixels	1024 x 768 in stripe configuration	Audio: RCA x 2 (L&R Stereo)	
Total Pixels	2,359,296 ((1024 x 768) x 3)	4. Video: RCA x 3 (Composite/Component: Y,Pb/Cb,Pr/Cr)S-Video x 1:	
Lens Type	Power Zoom and Focus	S-Video x 1; Audio: RCA x 2 (L&R Stereo)	
Lens Specs	Speed: f:1.6~2.1; FL: 1.91~2.46 in. (46.4~62.8 mm)	Outputs:Computer: Monitor	HD15 x 1 on Input 2 (switchable)
Lens Ratios	Zoom Max:Min: 1.3:1; Throw:Width1.82~2.37:1	Audio: External Speakers	5W x 2(Stereo) Push Terminal x 2 front
Image Diagonal	31~400 in. (78.8~1016cm)	Audio: Amplifier	Stereo: 3 Watts RMS Internal; 5 Watts RMS External
Image Width	2.07~26.7 ft. (0.63~8.2 m.)	Audio: Built in Speakers	Stereo:2 x 3.5in. (5 x 9cm.) x 2
Throw Distance	3.6~63.1 ft. (1.16m~19.23m.)	Fan Noise	39 dBA / 35 dBA in Eco-Mode
Front Elevation	up to 10.5° up	Size (HxWxD)	6.6 x 12.6 x 17.2 in. (168 x 319 x 435.2 mm.)
Anti Keystone	Power Lens Shift, Ratio (Top:Bottom) 10:0~1:1	Weight	19.6 lb. (8.9kg)
Vertical Keystone Correction	Digital: up to 40° up or down	Packaged Size (HxWxD)	13.3 x 17.8 x 24.9 in. (337 x 450 x 630 mm.)
Horizontal Keystone Correction	Digital: up to 10° left or right	Packaged Weight	29.7 lb. (13.5 kg.)
Scanning Frequency	Auto: H Sync.: 15-100kHz; V Sync.: 50-100Hz	Power Requirements	100-240V AC, 50/60Hz
Dot Clock	180 MHz	Power Consumption	450W/ (350 in Eco- mode)
Image Orientation	Normal, Reversed, Inverted	Heat	1536 BTU/hr. (387 Kcal/hr.) 1195 (301) in Eco- mode
Local Control / Power Management	Full Function / Auto Shut-Off	Power Cord	10' (3M) Type 3, Detachable
Remote Projector & Mouse Control	Wireless/wired with Laser Pointer x 1	Safety Compliance	UL, Listed
Ports: Mouse: USB x 1; Control 8-pin DINx1, Wired RC: MiniStereo x 1		Security Facilities	Kensington® Security Slot
Computer: Native Resolution	1024 x 768 (XGA)	Operating Temperature	41~95°F (5~35°C)
Computer: Compatibility	SXGA, XGA, SVGA, VGA, MAC	User Maintenance	Clean Air Filter, Replace Lamp
Computer: Formats	1280x1024, 1024x768, 800x600, 640x480	Warranty Projector	3 Yr/6000Hr *(Parts/Labor to Correct Defects)
Computer: Image Sizing	Normal, or Smart Compressed, or Expanded	Warranty Lamp	90 Days (Failed Lamp Replaced Pro Rata)
Video: System Compatibility	NTSC/PAL/SECAM/NTSC 4.43/PAL-M&N		* Which ever occurs first

Caution! Laser Radiation – Do not stare into beam. Max. Output: 1 mW. Wave Length: 660 +/- 20 nm. Class II Laser Product.

Lamp contains Mercury. Do not put in trash. Dispose of as Hazardous Waste, according to Local, State or Federal Laws.



205 Westwood Ave, Long Branch, NJ 07740

Phone: 866-94 BOARDS (26273) / (732)-222-1511

Fax: (732)-222-7088 | E-mail: sales@touchboards.com