

# LC-XB23

### **KEY FEATURES: Model LC-XB23**

Weighs less than 5.5 lbs! Footprint about the same as a sheet of paper!

2000 ANSI Lumens, 85% uniformity, and 400 contrast ratio.

3 panel LCD imaging delivers a rich, color saturated picture.

True XGA resolution. UXGA~VGA, and MAC compatible.

Quiet operation: fan noise as low as 29 dBA in Eco mode.

Smart data compression / expansion, and video scaling.

Convenient mid-range (1.2:1) manual zoom and focus lens.

Preset image offset. Vertical digital keystone correction.

Accepts Composite, S, and Component Video in all major standards.

Displays both 4:3 and 16:9 formats. Supports most HDTV resolutions. Converts Interlace to Progressive scan. 3-2 Pulldown support.

Variable Power Management option. Optional local or remote keylock.

VGA-type computer input. Slideshow Page Up/Down on remote control.

Custom warm-up screen image option. Factory defaults reset.

Wireless remote control. 7X digital zoom. Turn OFF and GO!


3 Year\* Projector Warranty!

Computer: Lower Resolution

#### **New Features:**

- 1. New cabinet is smaller and lighter: easier to carry, install, store.
- 2. Smaller, lighter shipping package: less expensive to ship.

## XGA "Brilliant" Series



LC-XB23

- 3. New compatibility with UXGA and WXGA (plus 2-2 pulldown for 575i).
- 4. Turn ON and Show! (Countdown can be optionally skipped.)
- 5. Turn OFF and GO! (AC power cord can be removed immediately after OFF.

Included Accessories: Owner's Manual. AC Power Cord. Lens Cover. VGA type Computer Input Cable (HD15 ~ HD15). Wireless Remote Control with & Batteries (AA x 2).

Displayed normal or Smart Expanded

Lamp:

Optional Accessories: Soft Carry Bag. Replacement Lamp. Remote Control with Laser Pointer. USB cable for slideshow Page Up / Page Down. Component Video Input Cable (HD15~3-RCA). MAC Adapter. MAC Monitor Cable. DB9~Mini Din-8 cable for RS-232 control. Luggage-Style ("wheelie") Carrying Case with Wheels, Telescoping Handle, and Detachable Computer Compartment. ATA-Style Shipping Case with Wheels and Telescoping Handle. Ceiling Mount. Ceiling Post and Plate. 33' (10m) Extension Cable for Serial Cable. EZ-250 Local Control. NPC-1 Network Control.

#### SPECIFICATIONS: Model LC-XB23

Screen Brightness 2.000 ANSI Lumens /1600 in Eco mode Illumination Uniformity Size of Color Palette 16.7 Million 400:1(Auto Lamp and Dynamic Image) (Full ON/OFF) Contrast Ratio 200 Watt UHP **Projection Lamp** Estimated Lamp Life up to 2000 Hours of Use Imaging System 0.6" PolySilicon active matrix TFT Panels x 3 Screen Pixels 1024 x 768 in stripe configuration **Total Pixels** 2,359,296 ((1024 x 768) x 3) Lens Type Manual Zoom and Focus Lens Specs Speed: f:1.65~1.81; FL: 0.886~1.063 in. (22.5~27 mm) Lens Ratios Zoom Max:Min: 1.2:1; Throw:Width: 1.79~2.15:1 Image Diagonal 40~300 in. (102~762 cm) Image Width 2.67~20 ft. (0.84~6.1 m.) Throw Distance (Wide / Tele) 4.6~43.3 ft. (1.4~13.2 m.) Front Elevation / Maximum Tilt up to 10° up / +/- 10° Anti Keystone Fixed Image Offset, Ratio (Top:Bottom) 10:1 Vertical Keystone Correction Digital: up to 20° up or down Scanning Frequency Auto: H Sync. 15-100kHz; V Sync. 50-100Hz Dot Clock 140 MHz Normal, Reversed, Inverted Image Orientation Local Control / Power Management Full Function / Auto Shut-Off Remote Projector Ctrl Wireless (Infra Red) x 1 Slideshow Page Up / Page Down Port USB type B x 1 Service Port (for RS-232 control) Mini DIN 8 Pin x 1 Computer Native Resolution 1024 x 768 (XGA) UXGA, SXGA+, SXGA, WXGA, XGA, SVGA, Computer: Compatibility VGA & MAC 1600 x 1200 through 640x480 Computer: Formats Computer: Higher Resolutions Displayed panned or Smart Compressed

Video: Compatibility NTSC / PAL / SECAM / NTSC 4.43 / PAL-M&N Video: HD Compatibility 480i/p, 575i/p, 720p, 1035i, 1080i Video: Formats Supported Normal 4:3 and Wide Screen 16:9 Video: Image Sizing Video Scaling Technology Image Signal Inputs \* Computer In 1 / Component In (with optional adapter) HD15 x 1 \* Computer In 2 / Monitor out (switchable) HD15 x 1 RCA x 1 (Composite) S-Video x 1 (Y/C) Video In: **Audio Signal Inputs** \* Computer 1 & 2 / Component Stereo: Ministereo x 1 \* Composite/S-Video RCA x 2 (L & R) Audio: Amplifier Mono: 1 Watt RMS Audio: Built In Speakers 1.1 in. (2.8 cm) x 1 Audio: Output Stereo: Ministereo x 1 (Variable) Fan Noise 34 dBA / 29 dBA (in Eco mode) Cabinet Size\*\* (HxWxD) 2.7 x 11.6 x 8.2in. (69.5 x 294.5 x 208mm.) \*\* excluding legs and lens 5.3 lbs. (2.4 kg) Weight Packaged Size (H x W x D) 9.6 x16.1 x14.2in. (244 x 409 x 361mm.) Packaged Weight 10.6 lb (4.8 kg) **Power Requirements** 100-240V AC, 50/60Hz 250 W / 205 W in Eco (9W in Standby) Power Consumption Heat 853 BTU/hr (215 Kcal/hr) / 700 BTU/hr (177 Kcal/hr) in Eco Power Cord 10' (3M) Type 3, Detachable Safety Compliance UL, cUL, IEC Security Facilities Kensington® Security Slot 41~95°F (5~35°C) **Operating Temperature** User Maintenance Clean Air Filter, Replace Lamp Warranty: (to the original end-use customer) 3 Yr. / 6000 Hr. \*(Parts & Labor to Correct Defects) Projector:

90 Days (Failed Lamp Replaced Pro-Rata)

\* Whichever occurs first