


Introducing the **NEW** HP-L1102 & HP-L3600

The Latest Table-Top type Overhead Projectors
A Quality Image for the Budget Conscious



[HP-L3600](#)



[HP-L1102\(Folded\)](#)

FEATURES

- **Easy storing for schools or rentals with foldable arm**
- **285mm (11.2") lens (HP-L1102)**
- **360mm (12.6") high resolution triplet lens (HP-L3600)**
- **10 x 10 in. aperture**
- **Rack and pinion focusing**
- **Quick lamp change device on both models**
- **Efficient open head with 360° rotation**
- **Stage interlock switch**
- **Safety thermal protection**
- **Forced air-cooling**
- **Metal & ABS body construction**
- **Writing roll attachment (option) easily mounted**
- **UL/cUL approved**

TOUCHBOARDS

Specifications

Model	HP-L1102	HP-L3600
Power Source	120V AC 60Hz	
Aperture Size	250 x 250mm (10 x 10 inches)	
Projection Lens	280mm (11 inches) single	320mm (12.6 inches) Triplet
Lens Head	Opens & Rotates 360°	
Projection Distance	1.5 ~ 3m (5 ~ 10 feet)	
Image Size	1.2 ~ 2.7m (4~ 9 feet)	1.0 ~ 2.0m (3~6 feet)
Projection Material	Transparency and writing roll	
Writing roll attachment (Option)	Useable ELMO sku # 4557	
Projection lamp	ANSI EYB 82V-360W (EYB-5 86V-360W lamp also usable)	
Quick lamp change device	Built-in	
Tilting angle adjustment	Up to 25°	
Forced air cooling	Forced-air cooling by motor fan	
Safety interlock switch	Built-in safety interlock switch cuts off power when stage frame is opened.	
Safety thermal cut-off switch	Built-in safety interlock cut-off switch automatically cuts off power to lamp if projector overheats.	
Dimensions		
-Folded	415mm (L) x 495mm (W) x 285mm (H) (16.3 x 19.5 x 11.2 inches)	
-Assembled	415mm (L) x 322mm (W) x 575mm (H) (16.3 x 12.7 x 22.6 inches)	
Weight	6.6kg (14.5 lbs.)	



ELMO Mfg. Corp.
1478 Old Country Road
Plainview, New York, 11803
Tel. 516.501.1400
Fax. 516.501.0429
www.elmousa.com

ELMO Canada Mfg. Corp.
44 West Drive, Brampton,
Ontario, L6T 3T6, Canada
Tel. 905-453-7880
Fax. 905-453-2391
www.elmocanada.com