

Specifications

SUV-Cam II

SUV-Cam PROFESSIONAL

Camera head	main unit	Water proofing	IPX8	
		Total length	80cm	
			150cm	
			-	300cm 500cm
		Mass	80cm=Approx.115g	
	150cm=Approx.150g			
	-		300cm=Approx.220g 500cm=Approx.310g	
	Dimension	diameter 20mm length 84.8mm		
	Lens	Focal length	3.8mm	
		F number	2.0	
		Horizontal field angle	53.4 °	
		Vertical field angle	40.0 °	
		Focus adjustment	Manual	
		Shooting range	0.5m to (factory setting)	
		Lens fixing	Lens stopper (Rubber spacer)	
Camera	Image pickup element	1/4 CCD		
	Total picture element	470,000 pixels		
	Effective number of pixels	440,000 pixels		
	min. object brightness	2 lx		
	White balance	Auto/Fixed		
	Electronic shutter	1/50 to 1/100,000 sec		
	Resolution	Horizontal 480TV Vertical 420TV		
	S/N ratio	48dB or more		
Recorder	main unit	LCD monitor	2.2 full color TFT LCD (QVGA)	
		Built-in microphone	Monaural microphone (Built-in)	
		Recording medium	SD card (Compatible with FAT12 and FAT16)	
			SDHC card (Compatible with FAT32)	
		File format	asf.	
		Moving image compressed format	Compliant with MPEG4	
		Audio compression format	Compliant with G.726	
		Vide output	NTSC/PAL (switches by the setting item.)	
		Audio input	Input impedance 2.2k?or more	
		Audio output	38mW + 38mW (Audio: Monaural) Load impedance 16?	
		USB	USB 2.0	
	Mass	Approx. 130g (when battery is installed)		
	Dimension	56mm (Horizontal) x 102mm (Vertical) x 30mm (width) (Exclude the projection part)		
	Terminal	Earphone/AV OUT	3.5 minijack (stereo)	
		External microphone	3.5 minijack (monaural) Plug-in power type	
DC IN		Dedicated jack		
Power supply part	main	Power supply	DC 3.7V(when the battery is used) DC 5.0V(when the AC adapter is used)	/
		Power consumption	2.8W(when the battery is used) 4.5W(when the AC adapter is used)	/
	Battery pack	Type	Lithium-ion battery (desorption type)	
		Nominal voltage	3.7V	
		Rating capacity	1660mAh	
		Mass	Approx.43g	
		Dimension	39mm (Horizontal) x 78mm (Vertical) x 9mm(width)	
	When battery detached	Power supply through AC adapter to recorder		
	AC adapter	Power supply	AC 100 - 250V 50 - 60Hz	
		Power consumption	DC 5.0V 2.0A	
		Mass	Approx.115g(Exclude the power code)	
		Dimension	53mm (Horizontal) x 76mm (Vertical) x 26mm (width)	
	Use environment	Operating temperature	0 ° C to 40 ° C(Camera Head -10 ° C to 50 ° C)	
Allowable relative humidity		10% to 80%		

Mass

