

Video Flex[®] Fume Hood 5400

The Ken-A-Vision® Video Flex® 5400 Fume Hood Camera was specifically designed with the Labconco Fume Hoods in mind. This easy-to-use flexible neck camera may be attached to, or removed from, the fume hood with ease. Simply attach the Video Flex Fume Hood Camera utilizing the pre-drilled hole on the Labconco Basic 47 Fume Hood. The camera may then be connected by external leads to a television monitor or multimedia projector; or simultaneously to a computer (USB connection) and then to a multimedia projector for multiple people to monitor activities inside the hood from a distance. When using a computer Applied Vision[™] Software (see extensive description over) may be used to capture and record experiments as single images, time-lapse sequences, time-lapse movies or continuous movies. The experiments may be recorded over a period of hours, days or weeks, limited only by the storage capacity of your computer.

With this unique fume hood setup and the video streaming feature of the software, events in a hood located in a laboratory can be observed in the comfort of a classroom some distance away!





Weight Weight Packed Box Dimension

Head Type Neck Length Lens Focus Focal distance Light Sensitivity Resolution 2 lbs / .91 kgs 4 lbs / 1.82 kgs 10"L X 3.5"W X 15"H 25 cm X 8.9 cm X 38 cm Ball and Socket 25" / 63.5 cm 8 mm ¹⁄₄ turn "Quick Focus[™]" ¹⁄₄" / 6mm to infinity 1.5 Lux 500 Lines

5400 SPECIFICATIONS

Magnification Output Singal

Software

Cable

Warranty

50:1 and greater USB (USB) Composite (Video) Applied Vision[™] Software for Windows[®] Ken-A-Vision[®] Capture for Macintosh[®] 6' (1.9 meters) USB 12' (3.7 meters) RCA 5 Years

Specifications subject to change without notice



Touchboards

205 Westwood Ave, Long Branch, NJ 07740 Phone: 866-94 BOARDS (26273) / (732)-222-1511 Fax: (732)-222-7088 | E-mail: sales@touchboards.com