

# DC150P

## Digital Visual Presenter

Function, style, and ease-of-use  
combined into one body,  
– the DC 150P is truly  
a “work of art”

*...offering a powerful impact  
that will liven up  
any classroom or boardroom*

- ▶ Gooseneck design allows lens and lamp heads to independently rotate 360 degrees, capturing images at all angles
- ▶ XGA resolution with razor sharp optics
- ▶ Large capture size up to 13" x 10"
- ▶ 20 frames per second
- ▶ Credit card size remote control



  
Brilliance by Design

# DC150P

## Digital Visual Presenter

- 32 page internal picture memory storage
- Adjustable swivel cold cathode fluorescent lamp allows rotation to avoid glare and shadows
- DVI output for best digital quality throughout
- USB connection for transferring captured images to PC
- Available in red or silver finish



## Specifications

(Subject to change without notice)

<b>Imaging</b>	Image Sensor	1/3" 850K progressive scan CCD
	Effective Pixels	1024 (H) x 768 (V), XGA
	Frame Rate	20 frames/second
	Shooting Area Size	10" x 13"
	Zoom	Mechanical 20x and 15x digital
	Focusing	Manual
	Capturing Modes	Presets for Photo / Text / Slide / Negative mode
	Image Rotation	Up to 180 degrees flip and rotation
	White Balance	Auto / Manual
	Exposure	Auto / Manual
Screen Freeze	Push button operation	
<b>Lighting</b>	Side Illumination	1 cold cathode lamp on arm
<b>Output</b>	RGB, Computer	D-sub 15 pin (VGA) RGB analog, XGA/SVGA 75Hz
	Synchronization	(H) 60k/47kHz, (V) 75Hz TTL level, positive polarity
	DVI	Digital & analog receptacles connector
	Composite Video	RCA jack, NTSC/PAL
	USB	Std. socket, type B
	DC 12V	DC jack, 500mA
<b>Input</b>	RGB, Computer	D-sub 15 pin (VGA)

<b>Special Features</b>	Image Memory	Up to 32 images can be captured by pushing the "Capture" button on the remote. An assortment of images can be instantly previewed and one image selected for full screen display. One or all of the captured images can be played back as a slide show with the remote control. The captured images can be transferred to a PC by the USB connection.
	Software	Software application for remote controlling and capturing via the USB connection between PCs and Lumens Camera. **MS-Windows only.
	Remote Control	Credit card size remote control with its own storage compartment.
	OSD	On Screen Menu Display available via control pad or remote control pad, remote control or attached PS/2 mouse.
<b>Accessories</b>	Included	Soft carrying case, remote control, DVI cable, DVI to VGA adapter, computer cable (VGA), USB cable, power cable, remote software and user manual CD
	Safety	UL, C-UL listed
	Regulatory	FCC Class A, CE
<b>General Specifications</b>	Power Requirements	AC auto switching 100-240 VAC, 50/60 Hz
	Power Consumption	18 Watts
	Dimensions	Open, 5.6" L x 8" W x 15" H
	Weight:	5.2 lbs (Shipping Weight 8 lbs)
	Warranty	2 years

**Lumens**™ . . . . .  
**Touchboards**

205 Westwood Ave, Long Branch, NJ 07740  
 Phone: 866-94 BOARDS (26273) / (732)-222-1511  
 Fax: (732)-222-7088 | E-mail: sales@touchboards.com

www.touchboards.com

205 Westwood Ave. Long Branch, NJ 07740

1-866-942-6273 Sales@touchboards.com