








Visual Presenter		DC80	DC130	DC150 Plus	PS350	PS550	PS600
 <p>205 Westwood Ave, Long Branch, NJ 07740 Phone: 866-94 BOARDS (26273) / (732)-222-1511 Fax: (732)-222-7088 E-mail: sales@touchboards.com</p>							
Price	MSRP (USD)	\$799	\$945	\$1,165	\$2,145	\$2,545	\$2,995
Imaging	Image Sensor	1/3" 850K progressive CCD	1/3" 850K progressive CCD	1/3" 850K progressive CCD	1/3" 850K progressive CCD	1/3" 850K progressive CCD	1/3" 850K progressive CCD
	Effective Pixels	1024 (H) x 768 (V), XGA	1024 (H) x 768 (V), XGA	1024 (H) x 768 (V), XGA	1024 (H) x 768 (V), XGA	1024 (H) x 768 (V), XGA	1024 (H) x 768 (V), XGA
	Frame Rate	20 fps	20 fps	20 fps	20 fps	20 fps	20 fps
	Shooting Area Size	10"x13"	10"x13"	10"x13"	11"x17" (8.5"x11" for transparency)	11"x17" (8.5"x11" for transparency)	11"x17" (4"x5" for transparency)
	Zoom	6x Mechanical, 16x Digital	20x Mechanical, 15x Digital	20x Mechanical, 15x Digital	Motorized 12x optical and 4x Mechanical	Motorized 12x optical and 4x Mechanical	Motorized 12x optical and 4x Mechanical
	Focusing	Manual adjustment	Manual adjustment	Manual adjustment	Automatic/Manual	Automatic/Manual	Automatic/Manual
	Capturing Modes	Presets for Photo/Text/Negative	Presets for Photo/Text/Negative	Presets for Photo/Text/Negative	Presets for Photo/Text/Slide/Negative and Microscope mode	Presets for Photo/Text/Slide/Negative and Microscope mode	Presets for Photo/Text/Slide/Negative and Microscope mode
	Image Rotation	180 degrees	180 degrees	180 degrees	180 degrees	180 degrees	90/180/270 degrees
	White Balance	Automatic/Manual	Automatic/Manual	Automatic/Manual	Automatic/Manual	Automatic/Manual	Automatic/Manual
	Exposure	Automatic/Manual	Automatic/Manual	Automatic/Manual	Automatic/Manual	Automatic/Manual	Automatic/Manual
Screen Freeze	Push button operation	Push button operation	Push button operation	Push button operation	Push button operation	Push button operation	
Lighting	Side Illumination	1 cold cathode lamps to arm	1 cold cathode lamps on arm	1 cold cathode lamps on arm	2 cold cathode lamps on arms	2 cold cathode lamps on arms	2 cold cathode lamps on arms
	Back Light	3rd party optional	3rd party optional	3rd party optional	8.5"x11" built into the stage surface	8.5"x11" built into the stage surface	4"x5" built into the stage surface
Output	RGB Computer	VGA RGB analog	VGA RGB analog	VGA RGB analog	VGA RGB analog	VGA RGB analog	VGA RGB analog
	Synchronization	60k/47kHz (H) , 75Hz (V)	60k/47kHz (H) , 75Hz (V)	60k/47kHz (H) , 75Hz (V)	60k/47kHz (H) , 75Hz (V)	60k/47kHz (H) , 75Hz (V)	60k/47kHz (H) , 75Hz (V)
	DVI			DVI-I	DVI-I	DVI-I	DVI-I
	S-Video				Mini Din 4 pin, NTSC/PAL	Mini Din 4 pin, NTSC/PAL	Mini Din 4 pin, NTSC/PAL
	Composite Video		RCA jack, NTSC/PAL	RCA jack, NTSC/PAL	RCA jack, NTSC/PAL	RCA jack, NTSC/PAL	RCA jack, NTSC/PAL
	Audio					Stereo mini jack line out	Stereo mini jack line out
	USB		Std. socket, type B	Std. socket, type B	Std. socket, type B	Std. socket, type B	Std. socket, type B
Input	DC12V	DC jack, 500mA		DC jack, 500mA		DC jack, 500mA	DC jack, 500mA
	RGB Computer	VGA RGB analog	VGA RGB analog	VGA RGB analog	VGA RGB analog	VGA RGB analog	VGA RGB analog
	Mouse Port				Std. PS/2, menu and pointer	Std. PS/2, menu and pointer	Std. PS/2, menu and pointer
	RS-232/Ethernet				RS-232 D-sub 9 pin male	RS-232 D-sub 9 pin male	Ethernet and RS-232 D-sub 9 pin male
Special Features	Microphone Input					Stereo mini jack	
	Seamless Switching/PBP						Support Seamless switching between all input sources and picture-by-picture display
	Step Zoom						Hot key step zoom set various view size
	RGB/CMY Color						Support independent color matching
	Image Memory			32 page	32 page	32 page	32 page
	PC Card					Compact flash memory with adapter	Compact flash memory
	Software		Mac and PC	Mac and PC	Mac and PC	Mac and PC	Mac and PC
Remote Control			Credit card size remote	Credit card size remote with built-in storage	Credit card size remote with built-in storage	Credit card size remote with built-in storage	
Accessories	OSD	6 Mechanical buttons control all functions	On Screen Menu Display via multi-function	On Screen Menu Display via multi-function	On Screen Menu Display	On Screen Menu Display	On Screen Menu Display
	Included	Padded Carrying case, VGA cable, power cable and user manual CD.	Carrying case, VGA cable, USB cable, power cable and user manual CD.	Carrying case, DVI to VGA adapter, VGA cable, USB cable, power cable and user manual CD.	Padded Carrying case, VGA cable, USB cable, power cable, slide/negative film holder and user manual CD.	Padded Carrying case, VGA cable, DVI to VGA adapter, USB cable, power cable, slide/negative film holder and user manual CD.	Padded Carrying case, VGA cable, DVI to VGA adapter, USB cable, power cable, slide/negative film holder and user manual CD.
General Specifications	Optional				Microscope adapter	Microscope adapter	Microscope adapter
	Safety/Regulatory	UL, C-UL, FCC Class A, CE	UL, C-UL, FCC Class A, CE	UL, C-UL, FCC Class A, CE	UL, C-UL, FCC Class A, CE	UL, C-UL, FCC Class A, CE	UL, C-UL, FCC Class A, CE
	Power Requirements	AC auto switching 100-240 VAC, 50/60 Hz	AC auto switching 100-240 VAC, 50/60 Hz	AC auto switching 100-240 VAC, 50/60 Hz	AC auto switching 100-240 VAC, 50/60 Hz	AC auto switching 100-240 VAC, 50/60 Hz	AC auto switching 100-240 VAC, 50/60 Hz
	Power Consumption	8 watts	18 watts	18 watts	15/30 watts (Lamp off/on)	15/30 watts (Lamp off/on)	15/30 watts (Lamp off/on)
	Dimensions	Folded, 11.4"(L)x5.5"(W)x2.3"(H). Open, 11.4"(L)x5.5"(W)x16.5"(H)	Open, 5.6"(L)x8"(W)x15"(H)	Open, 5.6"(L)x8"(W)x15"(H)	Folded, 20"(L)x13.8"(W)x5.1"(H). Open, 25.2"(L)x13.8"(W)x25"(H)	Folded, 20"(L)x13.8"(W)x5.1"(H). Open, 25.2"(L)x13.8"(W)x25"(H)	Folded, 20"(L)x13.8"(W)x5.1"(H). Open, 25.2"(L)x13.8"(W)x25"(H)
	Weight	3.3lbs (Shipping weight 18 lbs)	5.2lbs (Shipping weight 8 lbs)	5.2lbs (Shipping weight 8 lbs)	9.8lbs (Shipping weight 18 lbs)	9.8lbs (Shipping weight 18 lbs)	9.8lbs (Shipping weight 18 lbs)
	Warranty	2 years	2 years	2 years	2 years	2 years	2 years