

TX542 – Multimedia Projector

Best in Class

Optoma's TX542 delivers best-in-class features and performance. Bright, high contrast images and the built-in 10-watt speaker system will capture your audience's attention. Features such as wired networking allows both remote management and control of the TX542. Equipped with the latest color processing technologies from Texas Instruments and user-friendly features, the TX542 is a fully loaded all-in-one digital multimedia projector.



Features

- Easy-to-read text – bright at 2800 ANSI lumens and 3000:1 high contrast ratio
- Built-in closed captioning
- Eco-friendly sub one watt standby mode
- Built-in 10-watt speaker system
- Remote management and control via RS-232 or RJ45
- Broad range of audio and video connectivity



Specifications

Display Technology
 Single 0.55" DMD DLP®
 Technology by Texas Instruments

Resolution
 Native XGA (1024 x 768)

Maximum Resolution
 UXGA (1600 x 1200)

Brightness (Typical)
 2800 ANSI Lumens

Contrast Ratio
 3000:1 (Full On/Full Off)

Lamp Life and Type
 4000/3000 Hours (STD/Bright)
 180W P-VIP

Throw Ratio
 1.6 to 1.92:1 (Distance/Width)

Projection Distance
 3.93' to 32.8' (1.2 to 10m)

Image Size (Diagonal)
 30" to 307" (0.92 to 9.21m)

Aspect Ratio
 4:3 Native, 16:9 and 16:10
 Compatible

Remote Control
 Fully Featured IR Remote with
 Mouse and Laser Pointer

Audio
 Two 5-Watt Speakers

Displayable Colors
 1.07 Billion

Offset
 115%

Uniformity
 85%

Computer Compatibility
 UXGA, WXGA, SXGA+, SXGA, XGA,
 SVGA, VGA Resized, VESA, PC and
 Macintosh Compatible

Video Compatibility
 NTSC, PAL, SECAM, SDTV (480i),
 EDTV (480p), HDTV (720p, 1080i/p)

Horizontal Scan Rate
 15.3 to 91.1 KHz

Vertical Refresh Rate
 25 to 85 Hz

Keystone Correction
 ±40° Vertical

Loop Through
 Monitor: D-Sub 15-Pin VGA Output
 Audio: Mini-Jack Output
 (Functional in Both Normal and
 Standby Modes)

Projection Lens
 F= 2.4-2.66, f= 18.2-21.8mm,
 1.2x Manual Zoom and Focus

User Controls
 Complete On-Screen Menu
 Adjustments in 23 Languages

I/O Connectors
 HDMI, Two VGA-In, VGA-Out,
 S-Video, Composite Video, Three
 Audio-In, Audio-Out, RJ45, RS-232
 and USB

Security
 Kensington® Lock, Security Bar and
 Keypad Lock

Projection Method
 Front, Rear, Ceiling Mount, Table Top

Weight
 6.4 lbs (2.9kg)

Dimensions (W x H x D)
 12.76" x 3.82" x 9.21"
 (324 x 97 x 234 mm)

Noise Level (STD/Bright)
 29dB/34dB

Operating Temperature
 41 to 104°F (5 to 40°C), 80% Max
 Humidity

Power Supply
 AC Input 100-240V, 50-60Hz,
 Auto-Switching

Power Consumption
 255 Watts (Bright), 233 Watts
 (STD), <1 Watt (Standby)

Warranty
 3 Years Optoma Express
 Replacement Service, 1 Year on
 Lamp

Standard Accessories
 AC Power Cord, VGA to VGA
 Cable, Remote Control, Batteries
 for Remote, USB Cable, Carrying
 Case, Lens Cap, CD-ROM User's
 Manual, Quick Start Card and
 Warranty Card

Optional Accessories
 Wireless Dongle, Ceiling Mount,
 HDMI Cable, VGA to Component
 Cable, S-Video Cable, Composite
 Video Cable, RS-232 Cable and
 Panoview™ Series Screens

UPC
 796435 41 127 5

Accessory Part Numbers
 Lamp: BL-FP180E
 Remote: BR-5030L
 Mount: BM-5001U