

U4-SERIES



INTRODUCING THE BRIGHTEST PROJECTORS IN THEIR CLASS: THE 3 LB.

PLUS

DLP

U4 SERIES FROM PLUS. WITH UP TO 1800 LUMENS AND A 2000:1

CONTRAST RATIO, THE U4 SERIES BOASTS IMAGERY THAT'S CRISPER,

CLEANER AND BRIGHTER THAN EVER. THE CEILING-MOUNTABLE U4 ALSO

COMES WITH AN ECO-MODE OPTION THAT LETS YOU SAVE BULB LIFE.

Up to 1,800 ANSI lumens corner-to-corner brightness

Only 3 pounds

Eco-mode lets you increase lamp life by 30%

Digital zoom instantly targets and enlarges the fine print at the touch of a button

Connects to virtually any computer or video source

Short-focus lens allows for big-screen presentations in cramped quarters

Digital keystone correction

Wireless remote control and built-in control panel

HDTV compatible

CompactFlash card slot available

PLUS Vision Corp.



Phone: 866-94 BOARDS (26273) / (732)-222-1511 Fax: (732)-222-7088 | E-mail: sales@touchboards.com

PLUS

U4-SERIES

	Specifications	U4-136		U4-232	
	Resolution	solution XGA, 1024 x 768 pixels		XGA, 1024 x 768 pixels	
	RGB Signal XGA (true) SXGA (compressed)			XGA (true)	
				SXGA (compressed)	
		SVGA/VGA (expansion	on/true)	SVGA/VGA (expansion/true)	
	Brightness	1500 Lumens		1800 Lumens	
	Contrast Ratio	1500:1 (Full on/off)		2000:1 (Full on/off)	
	Aspect Ratio 4:3, supports 16:9			4:3, supports 16:9	
	Projection Lens	F=2.6-2.9		F=2.6-2.9	Choose from a variety of portable presentation screens from PLUS. They will save the day in any presentation environment.
		f=27.5-33mm		f=27.5-33mm	
	1:1.2 Manual Zoo			1:1.2 Manual Zoom	
		Manual Focus		Manual Focus	
	Digital Keystone Correction +25/-35 degrees			+17/-22 degrees	
	Digital Zoom	10x		2x	
Light Resource		150-watt lamp, 1,500 hrs.		180-watt lamp, 1,500 hrs.	
		2,000 hrs. in Eco-mode		2,000 hrs. in Eco-mode	
	Color Palette 16.7 million co			16.7 million colors	
	Projection Positions	Front/rear, Table/ceiling 3.9-25.9 ft. / 1.2-7.9 m		Front/rear,	
				Table/ceiling	
	Projection Distance			3.9-38 ft / 1.2-11.6 m	
	Image Size	26"-200" diagonal		26"-300" diagonal	- Replacement Bulbs PLUS offers a wide array of replacement bulbs so you can carry a spare anywhere.
	Video Signal	NTSC3.58, NTSC4.43, PAL, PAL-M,		NTSC3.58, NTSC4.43, PAL, PAL-M,	
	PAL-N, PAL60, SEC		٨,	PAL-N, PAL60, SECAM,	
		YCbCr (NTSC, PAL),		YCbCr (NTSC, PAL),	
		YPbPr (480p, 720p,	1080i)	YPbPr (480p, 576p, 720p, 1080i)	
	Audio	Mono 0.5 watt		Mono 0.5 watt	
	Dimensions Excluding Lens and Stand:				
	Height	2.08 in./53 mm		2.08 in./53 mm	
	Width	7.5 in./190 mm		7.5 in./190 mm	
	Length	9.4 in./239 mm		9.5 in./242 mm	
	Weight	3.3 lb./1.5 kg		3.3 lb./1.5 kg	E CLO
	 Wireless remote control Power cable (6 ft./1.8 m) Video cable (6.5 ft./2 m) S-video cable (6.5 ft./2 m) 3.5 mm mini plug audio cable (6.5 ft./2 m) 3.5 mm stereo plug to RCA DVI to mini D-sub 15 pin (6.5 ft./2 m) 		 DVI-D ca 3.5 mm, 4 15-pin to Presente 	ping cases les (9-12 ft./2.7-3.6 m) ble (6.5 ft./2 m) 4-pole plug to RCA component cable (5 ft./1.5 m) 9 RCA component cable (10 ft./3 m) er-2-Go - laptop-free presentation system to-Go - output DVI from any laptop	Remote Controls Choose from a variety of wireless remotes to fit any presentation environment.



205 Westwood Ave, Long Branch, NJ 07740 Phone: 866-94 BOARDS (26273) / (732)-222-1511 Fax: (732)-222-7088 | E-mail: sales@touchboards.com

PLUS Vision Corp.