

SAMSUNG

TECHWIN

SAMSUNG DIGITall
everyone's invited™

Samsung Digital Presenter

SDP-950ST/DX



Compact

Easy To Carry...5.5kgs (Body only)
Saving Space in Your Conference Room



Professional Lens

- : The Brightest And Finest Picture Quality By 1/3" 850,000 Pixels PS(Progressive Scan) CCD
- : An Exclusive 12X Powered Optical Zoom Lens(F3.0, f=6.3~75.6mm)
- : The Fastest And Perfect Auto Focus / Depth of Field 250mm
- : Continuously Working Auto focus
- : 15 Frame Rate Per Second



Easier to Use

- : Convenient Digital Function
 - 90° / 180° / 270° / 360° Rotation (Zoom Available)
 - Image Split & Shift - Image Freeze
 - 3X3 Screen Display - 8 Frames Save
 - 8 Functions Preset upto 4 Conditions
 - Negative / Positive Image Conversion
- : The Most Versatile PC And AV Interface (USB, RS-232, Twain, Win/Mac)
- : Pull down Menu, Writing & Drawing on the Screen by PC Mouse (PS/2)



www.samsungpresenter.com

www.touchboards.com 205 Westwood Ave.Long Branch, NJ 07740 1-866-942-6273 Sales@touchboards.com



Samsung Digital Presenter **SDP-950 ST/DX**

SPECIFICATION	DESCRIPTION	SDP-950ST	SDP-950DX
OPTICAL SYSTEM	LENS, ZOOM	F3.0, f=6.3~75.6mm [12X POWERED OPTICAL ZOOM]	
	SHOOTING AREA	MAX: 297mm X 210mm [11.59 X 8.27 Inch], MIN: 32mm X 24mm [1.26 X 0.94 Inch]	
	FOCUS	AUTO FOCUS / MANUAL FOCUS	
	IRIS	AUTO / MANUAL	
VIDEO	ADAPTOR LENS	REMOVABLE	
	PICK-UP DEVICE	1/3" 850,000 PIXELS PSIPROGRESSIVE SCAN) CCD	
	TOTAL PIXELS	1,077(H) X 788(V)	
	EFFECTIVE PIXELS	1,024(H) X 768(V)	
	FRAME RATE	15 FRAMES/SEC	
	SYNC SYSTEM	INTERNAL SYNC.	
	RESOLUTION	VGA OUT - HORIZONTAL: 570TVL / VIDEO OUT - HORIZONTAL : 350TVL	
	S/N RATIO	48dB	
	VIDEO OUTPUT	C-VIDEO / S-VIDEO	
	VGA OUTPUT	1,024 X 768 [XGA] RGB COLOR / 800 X 600 [SVGA] RGB COLOR / 640 X 480 [VGA] RGB COLOR	
PC INTERFACE	WHITE BALANCE	AUTO / MANUAL	
	USB	BUILT-IN	
	RS-232C	BUILT-IN	
	APPLICATION SOFTWARE	WIN / MAC	
DIGITAL FUNCTIONS	GRAPHIC USER INTERFACE	PULL DOWN MENU, WRITING & DRAWING ON THE SCREEN BY PC MOUSE [PS/2]	
	IMAGE FREEZE	AVAILABLE	
	NEGATIVE/POSITIVE	SELECTABLE	
	IMAGE SAVE & RECALL	NOT AVAILABLE	8 FRAMES SAVE, 3X3 FRAMES MULTI-DISPLAY
	IMAGE SPLIT AND SHIFT	NOT AVAILABLE	2 IMAGES [SAVE / LIVE]
	IMAGE ROTATION	NOT AVAILABLE	SWITCHABLE BY 90°
LIGHTING SYSTEMS	PRESET SAVE	8 FUNCTIONS PRESET UPTO 4 CONDITIONS [ZOOM, FOCUS, IRIS, POSI/NEGA & etc.]	
	UPPER LAMP	SIDE ARM LAMPS	
	LOWER LAMP	BOTTOM LIGHT BOX	
TERMINALS	INPUT	VGA X 2	
		MOUSE X 1	
		VGA [15P DIN] X 2	
		S-VIDEO X 1 / C-VIDEO X 1 [RCA]	
	OUTPUT	USB X 1	
		RS-232C [9 PIN] X 1	
		SUPPLIED	
		+5 °C ~ +35 °C	
REMOTE CONTROLLER	OPERATION TEMPERATURE	30% ~ 90%	
OPERATION HUMIDITY	POWER SOURCE	AC 100V ~ 240V FREE VOLTAGE, 50/60Hz	
POWER CONSUMPTION	WEIGHT	50W	
WEIGHT		5.5Kgs [12.13lb]	
DIMENSION		510mm(W) X 575mm(H) X 410mm(D) [IN USE] / 20.1(W) X 22.6(H) X 16.1(D) Inch [IN USE]	
OPTIONAL ACCESSORIES		LCD MONITOR, CARRYING BAG, LIGHT BOX	

Rear Panel



Dimension

Front view



Side view



Option



: BAG-950

Deluxe carrying bag




: LCD-5500

You can preview your presentation.

www.samsungpresenter.com

Design and specifications are subject to change without notice.

■ DISTRIBUTED BY



SAMSUNG

TECHWIN

Touchboards

205 Westwood Ave, Long Branch, NJ 07740

Phone: 866-94 BOARDS (26273) / (732)-222-1511

Fax: (732)-222-7088 | E-mail: sales@touchboards.com

info/EUN-2002.05