




PRODUCT INFORMATION

DuPont™ ProShield® 50 Hooded Coverall. Lightweight microporous film garment designed for non-hazardous aerosols, light liquid splash, and dry particles. White coverall features a respirator fit hood, elastic wrists and ankles, a storm flap, and a pin lock slider zipper pull. Suitable for janitorial, sanitation, and light industrial applications.

ATTRIBUTES

Full Part Number	NB127SWHxx0025yy (xx=size;yy=option code) ?
Fabric/Materials	ProShield® 50
Design	Coverall w/ Hood, Elastic Wrists and Ankles
Seam	Serged
Color	White
Quantity/Box	25 per case
Sizes	SM, MD, LG, XL, 2X, 3X, 4X, 5X, 6X
Option Codes	00



SIZE TABLE

SIZE	SLEEVE LENGTH	CHEST WIDTH	INSEAM	FITS CHEST	FITS HEIGHT	INNER GLOVE SIZE	OUTER GLOVE SIZE
SM	31 1/4	21 1/2	26 1/2	29 3/4 - 33 1/4	5'0" - 5'7"	n/a	n/a
MD	32 1/4	23 1/2	26 1/2	33 3/4 - 37 1/4	5'3" - 5'7"	n/a	n/a
LG	33 1/4	25 1/4	27 1/2	37 1/4 - 40 3/4	5'5" - 5'9"	n/a	n/a
XL	35	27	28 1/4	40 3/4 - 44 1/4	5'8" - 6'2"	n/a	n/a
2X	36 1/4	28 3/4	28 3/4	44 1/4 - 47 3/4	6'0" - 6'4"	n/a	n/a
3X	37 1/2	30 1/2	29 1/4	47 3/4 - 51 1/4	6'2" - 6'4"	n/a	n/a
4X	37 1/2	32 1/4	29 1/4	51 1/4 - 54 3/4	6'4" - 6'7"	n/a	n/a
5X	40 1/2	34	29 3/4	54 3/4 - 58 1/4	6'7" - 6'10"	n/a	n/a
6X	40 1/2	35 1/4	29 3/4	57 1/4 - 60 3/4	6'9" - 7'1"	n/a	n/a



TECHNICAL DATA SHEET

PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL RESULT
Thickness	ASTM D751	7.6 mils
Basis Weight	ASTM D751	1.6 oz/yd ²
Tear Resistance - Trap Tear (MD)	ASTM D5733	6 lb _f
Tear Resistance - Trap Tear (CD)	ASTM D5733	13 lb _f
Breaking Strength - Grab (MD)	ASTM D5034	30 lb _f
Breaking Strength - Grab (CD)	ASTM D5034	18 lb _f
Hydrostatic Head	AATCC 127	>50 inches H ² O
Surface Resistivity (23°C / 25% RH)	EN 1149-1	Pass
Wearing Apparel Flammability	16 CFR 1610	Class 1

WARNING

*Serged and bound seams are degraded by some hazardous liquid chemicals, such as strong acids, and should not be worn when these chemicals are present.

*Liquid barrier performance varies based on the amount of liquid that may get on the garment, the length of time the liquid is on the garment, applied pressure and certain physical properties of the liquid. Tyvek®400, Tyvek® 400 D, ProShield®, ProShield® 10, ProShield® 60, Tyvek® 400 FC, and ProShield® 70 garments are not appropriate if during use they are getting wet (liquid is dripping or running, or it is wet to the touch) or if spotting is observed on skin or garments worn under the protective garment. Tyvek® 500 and Tyvek® 600 offer improved liquid barrier, but may not be appropriate if spotting is observed on the skin or garments worn under the protective garment. In applications where a higher liquid barrier is needed, consider Tychem® 2000 and Tychem® 4000 garments with taped seams.


*CAUTION: This information is based upon technical data that DuPont believes to be reliable. It is subject to revision as additional knowledge and experience are gained. DuPont makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics, not complete garments, under controlled conditions. It is intended for informational use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher permeation rates than the fabric. Please contact DuPont for specific data. If fabric becomes torn, abraded or punctured, or if seams or closures fail, or if attached gloves, visors, etc. are damaged, end user should discontinue use of garment to avoid potential exposure to chemical. Since conditions of use are outside our control, we make no warranties, express or implied, including, without limitation, no warranties of merchantability or fitness for a particular use and assume no liability in connection with any use of this information. This information is not intended as a license to operate under or a recommendation to infringe any patent or technical information of DuPont or others covering any material or its use.

Cellosolve® and Selexol™ are registered trademarks of Dow Chemicals Company. Skydrol® is a registered trademark of Solutia.

As of January 2023, all DuPont Personal Protection products are manufactured under specifications that exclude components containing natural rubber latex. Tyvek® 500, Tyvek® 600 and Tyvek® 800 styles made before January 2023 contain natural rubber latex, which may cause allergic reactions in some sensitized individuals. Anyone who begins to exhibit an allergic response during the use of DuPont products should immediately cease using these products and should report it to DuPont at +1 (888) 439-2988 so that an investigation can be initiated.

DuPont™ SafeSPEC™ - We're here to help

Our powerful web-based tool can assist you with finding the appropriate DuPont garments for chemical and controlled environment hazards.





DuPont Personal Protection SafeSPEC™

 [DuPont Personal Protection](#)

 [DuPont Personal Protection](#)

CREATED ON: FEBRUARY 27, 2026