

DuPont™ Tyvek® 800



Liquid-tight protection with the comfort and durability of Tyvek®



This garment is ideal for situations that require protection from heavy liquid spray, even in a pressurized jet form.

- Effective barrier against many water-based inorganic chemicals in low concentration and particles (down to 1.0 micron in size)
- Tyvek® 800 fabric with taped seams has been tested and has passed the requirements of ASTM F1670 and ASTM F1671, the recognized blood and viral penetration test methods in North America
- Protection against infective agents (EN 14126), including resistance to penetration by blood and body fluids using synthetic blood (ISO 16603) and resistance to penetration by blood-borne pathogens using Phi-X174 bacteriophage (ISO 16604)
- Oil repellent

Please visit our free online DuPont™ SafeSPEC™ selector tool to help you determine the most appropriate protection based on your hazard risk assessment.

safespec.dupont.com



Industrial
cleaning



Chemical
handling



Waste
management



Environmental
remediation



Pharmaceutical
applications*

Reference: TJ198T

Color: White

Size: SM-7X

*Hazardous powders & cytostatic chemicals



Where does Tyvek® 800 fit in our portfolio?

Tyvek® 800 resides between Tyvek® 600 and Tychem® 2000 serged seam offerings.



Standard Tyvek®

Tyvek® 800 provides better liquid protection.


Tyvek® 800

With a Tyvek® base, added chemical protection and taped seams.

DuPont™ Tychem® 2000

Tyvek® 800 offers comfort advantages over Tychem® 2000 due to weight and water vapor permeability.

NOTE: The user must ensure suitable reagent to garment compatibility before use. Visit safespec.dupont.com to determine the most appropriate DuPont protective garments for your chemical hazard.



DuPont™ SafeSPEC™—we're here to help

Our powerful web-based tool can assist you with finding the appropriate DuPont garments for chemical, controlled environment, thermal and mechanical hazards. safespec.dupont.com



Certified Industrial Hygienist team

A DuPont Certified Industrial Hygienist can conduct a job hazard assessment to help you determine the best DuPont garment for a specific hazard.



DuPont Personal Protection
Customer service 1 800 931 3456
safespec.dupont.com
personalprotection.dupont.com

DuPont Personal Protection
DuPont™ Tyvek®

This information is based upon technical data that DuPont believes to be reliable. It is subject to revision as additional knowledge and experience become available. It is the user's responsibility to determine the level of toxicity, and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics, not complete garments, under controlled conditions. This information is intended for use by persons having the technical expertise to undertake evaluation under their own specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first check that the garment selected is suitable for the intended use. The end-user should discontinue use of garment if fabric becomes torn, worn or punctured, to avoid potential chemical exposure. Since conditions of use are beyond our control, DUPONT DE NEMOURS, INC. AND ITS AFFILIATES MAKE NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND ASSUME NO LIABILITY IN CONNECTION WITH ANY USE OF THESE PRODUCTS AND INFORMATION. This information is not intended as a license to operate under or a recommendation to infringe any trademark, patent or technical information of DuPont or other persons covering any material or its use.

© 2026 DuPont. All rights reserved. DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with TM, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted.