

NEW

HM 50

Portable Handheld Pin Moisture Meter

- Easy To Use
- Compatible with Wood Type 1, Wood Type 2, Plaster & Brick / Concrete
- HOLD Function
- 20 Minute Auto Shut-Off
- 2-Line Display

Parameter	Material	Detail	Range	Accuracy*
M1	Wood Type 1	Birch, Beech, Spruce, Larch, Walnut, Cherry	10 to 90%	±1%
M2	Wood Type 2	Oak, Pine, Maple, Ash, Pine Douglas	9 to 90%	±1%
M3	Plaster	N/A	0.1 to 15%	±1%
M4	Brick / Concrete	N/A	0.1 to 15%	±1%

Conditions of Use	32°F to 122°F / 0°C to 50 °C In Non-Condensing Conditions 0 to 6550 ft / 0 to 2000 m
Storage Temperature	-4°F to 176°F -20°C to 80 °C
Power Supply	4 AAA Batteries LR03 1.5 V
Battery Life	180 Hrs
European Directives	2014/30/EU EMC ; 2014/35/EU Low Voltage ; 2011/65/EU RoHS II ; 2012/19/EU WEEE

*All the accuracies indicated in this technical datasheet were stated in laboratory conditions, and can be guaranteed for measurements carried out in the same conditions, or carried out with calibration compensation



Material: ABS

Protection: IP54

Display: 2 Lines

Size: 2.8 x 1.3 x 5.8 in

Weight: 7 oz

(w/ batteries)