ECO X26N

Model	ECO X26N
Technology	.63" 3 x TFT LCD Panels
Brightness	2600 lumens (standard) / 1800 lumens (economy)
Native Resolution	1024 x 768 (XGA)
Supported Resolution	up to 1600 x 1200 (UXGA)
Brightness Uniformity	85%<
Projection Methods	Desktop front/rear, Ceiling front/rear
Optical Offset	9:1
	4000:1
Contrast Ratio Aspect Ratio	
	Native 4:3; Compatible 16:9
Image Size	40 in ~ 300 in
Projection Distance	Wide: 46.2 in ~ 352 in / 1.174 m ~ 8.943 m Tele: 55.6 ~ 422.7 in / 1.413 m ~ 10.737 m
Throw Ratio	1.45 ~ 1.73:1 *allow 3-5% variance on all throw ratios
Speaker	1 x 7W
Zoom Ratio	1.2:1
Digital Zoom	1/4 ~ 16
Keystone Correction	Auto +/- 30 degrees
Horizontal Scan Rate	15 ~ 100 kHz
Vertical Scan Rate	48 ~ 85 Hz
Lens Type	Manual zoom / focus
Lamp	Ushio 230W
Lamp Life	4000 hr (standard) / 6000 hr (economy)
Remote Control	Multi-function remote with battery
Noise Level	36db@1m (standard) / 32db@1m (economy)
Power Supply	100 ~ 240V AC @ 50 ~ 60Hz
Power Consumption	280W (standard) <.5W in standby mode
Safety Certifications	CE, CCC, CB, CECP, cTUVus, FCC
Computer Compatibility	UXGA, WXGA, SXGA, XGA, SVGA, VGA PC and Macintosh compatible
Video Compatibility	PAL, SECAM, NTSC 4.43, PAL-M, PAL-N 480i/p, 576i/p, 720p, 1035i, 1080i
Colors	16.7 million
Inputs	S-video x 1, component x 1, video x 1 (share with component video), VGA x 2 (2nd VGA is optional in/out), 3.5mm audio x 1, RCA (L/R) x 2, HDMI x 1
Outputs	VGA x 1 (optional in/out), 3.5mm audio x 1
Service and Network Control	RS232, RJ45
Weight	6.4 lbs / 2.9 kg
Dimensions (W x H x D)	12.9 in x 9.5 in x 3.4 in / 327 mm x 241 mm x 87 mm
Operating Conditions	5°C ~ 35°C, Storage (-10°C ~ 60°C)
Security	Kensington® lock port, anti-theft bar, keypad lock
Standard Accessories	AC power cord, VGA cable, remote control with battery, user manual (CD), lens cover with string



205 Westwood Ave, Long Branch, NJ 07740 Phone: 866-94 BOARDS (26273) / (732)-222-1511 Fax: (732)-222-7088 | E-mail: sales@touchboards.com




BOXLIGHT's ECO Series Projectors

The Eco projector series for non-interactive applications. The first of BOXLIGHT's new projector line focusing on affordable, basic classroom projection.

KEY FEATURES

- Auto keystone
- Multiple display modes
- Variable iris
- Blank screen hot key
- Freeze function
- Closed captioning
- Multiple anti-theft features
- 10 second start up
- 60 second cool down
- On-screen timer



Award Winning Technical Support 24/7/365

BOXLIGHT products come with free lifetime technical support. Speak with a hands-on, in-house, ISF Certified® technician ready to service your projector should the need arise.



